

Item no.: 323730

BEACON I6 - Sticker Beacon, BT 4.0, iBeacon

from 6,95 EUR

shipping weight: 0.10 kg
Manufacturer: MINEW Technologies



Product Description

Beacon i6 - Sticker Beacon, BT 4.0, iBeaconThe i6 is an ultra-thin iBeacon with ARM core chipset nRF51822 a BLE 4.0 technology. The device runs with the standard MiniBeacon

Features

- Programmed MiniBeacon standard firmware
- Ultra-thin, only 3.3 mm
 Max. 50 meters transmission distance
- Small size, user-friendly and portable
- Compatibility: Supports iOS 7.0+, Android 4.3+, Apple iBeacon(TM) standard, Bluetooth 4.0 (BLE) devices
- Battery Lifetime: 6 months, real-time battery level notification
 OTA and J-Link: Supports OTA, reserved J-Link port on the board for programming
- Configurable Parameters: UUID, major, minor, device name, password etc., special configuration app Transmission Power Levels: 8 adjustable levels, range from 0 to 7

- Transmission Power Levels: 8 adjustable levels, range from 0 to 7
 Transmission Power Range: -30 dBm to +4 dBm
 Soft Reboot: Reboot the device via command without any tools
 Connection Mode: Advertising mode, non connectable, configuration mode, connectable
 Mounting: 3 m brand adhesive for direct mounting to wall
 Shape: Ultra-thin 3.3 mm, battery replaceable design

- Case Color: White, can be customized

 Battery Model: 1x CR2016 coin battery, 3 V (not included)

 Operation Voltage: 1.8 3.6 V
- Transmission Circuit: 10.5 mA (max.)
 Transmission Range: Max. 50 meters
- Antenna: 50 ohm, on board, PCB antenna
 Accessories: Double-sided adhesive tape
- Weight: 4 g, with battery
 Size: 32 x 23 x 3.3 mm

Specifications

