

Item no.: 323852

RBA-12-AS4-CAX-A6 - 19" Wall Cabinet, Ventilation Openings, 12 U, 395 mm Depth

from **230,54 EUR**

Item no.: 323852
shipping weight: 19.50 kg
Manufacturer: Triton



Product Description

19" Wall Cabinet, Ventilation Openings, 12 U, 395 mm Depth

Rigid Construction

High-quality workmanship and up-to-date technology ensure a perfect look of the cabinet.

Door

The cabinet has a full glass door as a standard feature. However, if required it can be delivered with steel or perforated door.

Flexible Door Opening

The hinge system allows the door to open almost 180°. The door can be easily removed and re-mounted to change the direction of opening.

Door Lock

It enables an easy and quick access into the cabinet.

Adjustable Vertical Rails

One pair of vertical 19" rails is freely adjustable in any depth of the cabinet. This simplifies cable management and the mounting of devices.

Breakout-Type Blanking Panels

Cable openings covered with breakout-type blanking panels are in the top, bottom and rear part of the cabinet. Part of the additional supplies is a fringe edge and a blanking panel with a brush to seal the cabinet opening against ingress of dust.

Ventilation

The RBA type A6 has 6 break-out blanking panels for the installation of ventilation units RAX-CH-X2x-X1 (up to 3 in top and 3 in bottom part of the cabinet). Now, you can install components into RBA cabinets that, in the past, could not be cooled in wall cabinets and had to be installed in standing cabinets instead.

Measurements:

- Height 635 mm x width 600 mm x depth 395 mm

Supply includes:

- 2x key - front door
- 4x screw 6x50
- 4x washer 6,6
- 4x dowel 10
- 8x captive nut M6
- 1x blanking panel with brush

Material:

- Safety glass, tempered, 4 mm thick
- Deep drawn sheet steel
- 19" one-sectioned wall-mounted cabinet with IP30 protection
- Cabinet is to be hanged right on the wall
- Cabinet includes two sliding vertical rails
- Cabinet construction: compact welded cabinet, tempered safety glass door, thickness 4 mm. May be metal or perforated on demand.
- Max. permissible load of the door is 10 kg
- Cabinets are intended for installation of data and telecommunication devices and their distribution systems
- The frame of the cabinet and all the removable parts (side and rear covers, doors) are connected with grounding cables that have to be properly attached and inserted into the connectors at all times while using the cabinet
- There is one M8 screw placed at the bottom part of the cabinet as a grounding point
- Cable openings covered with break-out blanking panels are located in the top and the bottom part of the cabinet's rear side, others are in the top and the bottom side of cabinet
- The A6 version has several openings in the top and bottom part of the cabinet that allow to install ventilation units and which are covered with break-out blanking panels

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

