

Item no.: RBSXTR

RBSXTR - SXT R with 10.5 dBi 60 degrees LTE directional antenna

64,12 EUR

Item no.: RBSXTR
shipping weight: 0.80 kg
Manufacturer: MikroTik



Product Description

MikroTik RBSXTR - SXT R with 10.5 dBi 60 degrees LTE directional antenna

The SXT R is a device for remote locations within mobile network coverage. However, due to its high gain antenna, it can provide connections for your building even if mobile phones cannot.

In comparison with MikroTik's first generation model RBSXLTLE3-7, the SXT LTE kit is powered by faster CPU and supports not only LTE with more speeds, but also 2G (international model only) and 3G, as well as a much wider band range. The unit is equipped with two Ethernet ports (the second port has PoE-out functionality), so you can use it to power up another device. The unit is shipped with a 24 V power supply, but can support full range 18-57 V and is 802.3af/at compliant.

The device has a built in high quality Category 4 modem for speeds of up to 150 Mbit/s downlink and 50 Mbit/s uplink, as well as two Micro SIM slots for backup link. SXT R (RBSXTR) doesn't include any LTE modem (free miniPCI-e slot) - antenna only version, to be used with custom LTE modem.

- Product code: RBSXTR
- CPU: QCA9531 650 MHz
- Size of RAM: 64 MB
- Storage: 16 MB Flash
- 10/100 Ethernet ports: 2
- LTE antenna gain: 10.5 dBi
- Antenna beam width: 60°
- LTE category: -
- 3G category: -
- 2G category: -
- SIM slots: 2 (Micro SIM)
- PoE in: Yes, on Ether1
- PoE out: Yes, on Ether2, max. output per port (input: 30 V): 400 mA; max. total output (A): 600 mA
- Supported input voltage: 18 - 57 V (passive PoE, 802.3af/at on Ether2)
- Dimensions: 140 x 140 x 103 mm
- Operating temperature: -40°C to +60°C tested
- License level: 3
- Operating system: RouterOS
- Max. power consumption: 6 W

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

