

Item no.: 325995

ARCHER T2U PLUS - AC600 High-Gain Dual Band USB WLAN Adapter

from **18,04 EUR**

Item no.: 325995
shipping weight: 0.20 kg
Manufacturer: TP-LINK



Product Description

TP-Link Archer T2U Plus - AC600 High-Gain Dual Band USB WLAN Adapter

The Archer T2U Plus receives the wireless signal from two separate bands. With 256QAM support, wireless LAN speed in the 2.4 GHz band increases from 150 Mbps to 200 Mbps. It is ideal for home networking. At 433 Mbps in the 5 GHz band, the Archer T2U Plus is also an excellent choice for seamless HD streaming, online gaming and other bandwidth-intensive tasks. [Larger Wi-Fi coverage](#)

Thanks to its external 5 dBi high-gain antenna, the Archer T2U Plus has better Wi-Fi reception and stronger transfer signal. [Detachable, high performance, multidirectional antenna for maximum range](#)

The Archer T2U Plus has a detachable and multidirectional high-performance antenna to ensure greater signal transmission and reception.

Hardware

- Interface: USB 2.0
- LED: Status
- Dimensions (W x D x H): 57.8 x 18 x 173.4 mm
- Antenna: 5 dBi

WLAN

- Standards: IEEE 802.11b/g/n 2.4 GHz, IEEE 802.11a/n/ac 5 GHz
- Speeds: 600 Mbps (200 Mbps at 2.4 GHz, 433 Mbps at 5 GHz)
- Frequency: 2.4 GHz, 5 GHz
- WLAN modes: Ad hoc/infrastructure mode
- WLAN security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
- Modulation methods: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

Miscellaneous

- Certifications: FCC, CE, RoHS
- Package contents: AC600 high-gain dual-band USB WLAN adapter Archer T2U Plus; Quick start guide; Resource CD
- System requirements: Windows 10/8.1/8/7/XP, Mac OS X 10.9-10.13 (beta for 10.14)
- Environment: Operating temperature: 0°C ~ 40°C (32°F ~ 104°F); Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

