

Item no.: 330553

CM2-24-58-2RPSP - Ultra low profile MiMo, WiFi antenna

60,96 EUR

Item no.: 330553

shipping weight: 0.30 kg

Manufacturer: Panorama Antennas



Product Description

CM2-24-58-2RPSP Ultra low profile MiMo, WiFi antenna
The CM[X]-24-58-2 series was developed to enable MiMo WiFi operation in an ultra low profile housing. The compact, robust and flat housing contains up to four antenna elements with effective isolation and low correlation, covering 2.4-2.5/4.9-6 GHz. The antenna is designed to be mounted on vehicles or fixtures and can be mounted on a conductive or non-conductive plate. The antenna is supplied with integrated flame retardant CS32 cables (according to UNECE 118.01 and EN45545-2) and a halogen-free flame retardant radome and is suitable for many environments and applications.
Features- Ultra Low Profile- Up to 4 x 4 MiMo Dual Band WiFi Dual Band WiFi- Certified to EN4554545-2- Certified to EN50155- Complies with IP69K and IK10 Electrical data- WLAN frequencies: 2.4/5.0 GHz- Typical VSWR: - WiFi MiMo: 2x2- Maximum input power (W): 10- Pattern: Omnidirectional- Baseplate independent: Yes
Mechanical data- Available colour: White- Height (mm): 30- Diameter (mm): 115- Connection: Rev Pol SMA plug
Mounting data- Mounting type: Panel mount- Mounting method: 18mm (3/4") mounting socket
Approval data- Vandalism protection: IK10- IP protection class: IP66/IP69K- Flame protection: UN118.01 / EN6722 / EN455454545- Industrial approvals: EN4554545

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

