

Item no.: 330541

LGMM4-7-38 - Low Profile 4x4 MiMo Antenna

from **220,70 EUR**

Item no.: 330541
shipping weight: 0.60 kg
Manufacturer: Panorama Antennas



Product Description

Low Profile 4x4 MiMo Antenna LGMM4-7-38

The LGMQM4 is a range of high-performance MiMo antennas covering 698-3800MHz as well as offering 2x2 / 3x3 or 4x4 MiMo/Diversity at 2.4/5.0GHz and a GNSS antenna. The Panorama L[G]M[Q]M4 low profile MiMo antenna range has been designed to support the next generation of vehicular LTE routers with 4x4 MiMo. The antenna enclosure can provide up to nine antenna elements.

All versions have four ultra-wideband elements for 698-3800MHz which support MiMo function for 4G/5G & cellular bands. LG versions offer a GNSS antenna which has a 26dB gain LNA with high performance filtering for reliable operation. Variants are also available which include 2, 3 or 4 dual band 2.4/4.9-6GHz WiFi elements for MiMo function designated by the suffix 24-58.

The antenna does not require a metallic ground plane, and maintains a high level of performance even when mounted on a non-metallic surface. The GNSS antenna module carries an E11 Mark type approval under ECE R10.4, and the cables are certified to ECE 118.01.

Although the LTE elements are designed for 4x4 MiMo operation, it is possible to utilise these as 2 pairs of 2x2 MiMo for a router that has 2 SIMS (radio) in a failover configuration (i.e. only one SIM active at any time). As this configuration is using only 2 out of the 4 antennas for a single SIM, the network coverage should be checked to ensure that this use is suitable.

Guidance on correct connection of the LTE antennas is provided in the installation instructions. Please Note: This antenna is not intended for use with a router that has 2 SIMS to provide concurrent or aggregated data operation, as there is not sufficient isolation between the MiMo pairs.

Features

- Designed for use with LTE Advance Pro
- Low profile antenna with up to 9 functions in 1
- MiMo 2G/3G/4G Cellular, MiMo 2.4/4.9-6GHz and GNSS in one housing

Electrical Data

- LTE Frequencies: 698-960/1710-3800MHz
- Global Positioning: GPS/GNSS 1562-1612
- Wifi: No
- LTE MiMo: 4x4
- WiFi MiMo: No
- Max Input Power (W): 10
- Pattern: Omni-directional
- Ground Plane Independent: Yes

Mechanical Data

- Colour: White
- Height (mm): 48
- Diameter (mm): 170
- Operating Temperature: -30/+80°C

Mounting Data

- Mounting Type: Panel Mount
- Mounting Method: 19 mm (3/4") Mounting Bush

Approvals Data

- IP Rating: IP69K

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

