

Item no.: 332958

TL-SL1226P - Unmanaged PoE/PoE+ Switch

from **265,84 EUR**

Item no.: 332958
shipping weight: 3.00 kg
Manufacturer: TP-LINK



Product Description

TL-SL1226P - Unmanaged PoE/PoE+ Switch

TP-Links new PoE/PoE+ switches with all 10/100 Mbps RJ45 ports supporting the PoE+ standard provides a simple way to expand the wired network while transferring power over the same Ethernet cable at the same time. With up to 30 W per port, TL-SL1218MP and TL-SL1226P can power more high-powered devices such as access points, IP cameras, IP phones and so on. Moreover, with innovative Extend Mode, devices can get PoE power supply and data transmission from a distance of 250 m. Priority Mode ensures high priority for port 1–8, which guarantees the quality of sensitive applications. TL-SL1226P supports Isolation Mode that divides traffic for ports 1–24 for higher security and performance.

General

- Interfaces: 24x 10/100 Mbps RJ45 ports; 2x 10/100/1000 Mbps RJ45 ports; 2x combo Gigabit SFP slots

PoE

- PoE standard: 802.3af/at
- PoE ports: 24, up to 30 W
- PoE power budget: 250 W

Performance

- Switching capacity: 8.8 Gbps
- Packet forwarding rate: 6.54 Mpps
- MAC address table: 8 K
- Packet buffer: 4.1 Mbit
- Jumbo frame: 10 KB

Physical & Environment

- Power supply: 100–240 V AC, 50/60 Hz
- Max. power consumption: 281 W (with 250 W PD connected), 17.17 W (no PD connected)
- Max. heat dissipation: 958.21 BTU/h (with 250 W PD connected), 58.55 BTU/h (no PD connected)
- Dimensions: (W x D x H): 17.3 x 7.1 x 1.7 in.(440 x 180 x 44 mm)
- Fan quantity: 2
- Operating temperature: 0°C – 50°C (32°F – 122°F)
- Storage temperature: -40°C – 70°C (-40°F – 158°F)
- Operating humidity: 10% – 90% RH non-condensing
- Storage humidity: 5% – 90% RH non-condensing
- Certification: CE, FCC

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



