

Item no.: 332952

TL-POE2412G - Passive PoE Adapter

20,57 EUR

Item no.: 332952
shipping weight: 0.30 kg
Manufacturer: TP-LINK



Product Description

TL-POE2412G - Passive PoE Adapter

The passive PoE adapters TL-POE2412G and TL-POE4824G can be used to simultaneously supply power and transmit data to a passive PoE device. For example, TL-POE2412G can be used with TP-Link's EAP225 3.0 and CPE610, and TL-POE4824G can be used with EAP245 3.0.

TL-POE2412G offers a convenient wall-mounting brackets to be easily installed on a wall.

- Model: TL-POE2412G
- Interface: 2x 10/100/1000 Mbps RJ45 ports; Auto Negotiation/Auto MDI/MDIX; 1x AC power input port
- Network media: 10BASE-T: UTP category 3, 4, 5 cable (max. 100 m); EIA/TIA-568 100 Ohm STP (max. 100 m); 100BASE-TX: UTP category 5, 5e cable (max. 100 m); EIA/TIA-568 100 Ohm STP (max. 100 m); 1000BASE-T: UTP category 5, 5e, 6 cable (max. 100 m)
- Output voltage: 24 V DC (max. 12 W)
- LED indicator: Power
- Dimensions: (W x D x H): 3.4 x 1.7 x 1.4 in. (85.8 x 43.9 x 35 mm)
- Certification: FCC, CE, RoHS
- Package contents: 24 V 12 W passive PoE adapter TL-POE2412G, power cord, wall mounting kits
- Environment: Operating temperature: 0°C ~ 40°C (32°F ~ 104°F); Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

