

Item no.: CRS326-24G-2S+IN

CRS326-24G-2S+IN - Cloud Router Switch with 800 MHz CPU, 512 MB RAM, 24x Gigabit LAN, 2x SFP+

from **184,57 EUR**

shipping weight: 1.70 kg Manufacturer: MikroTik



Product Description

CRS326-24G-2S+IN - Cloud Router Switch with 800 MHz CPU, 512 MB RAM, 24x Gigabit LAN, 2x SFP+

A home network setup doesnt have to be a compromise. This compact and quiet switch is packing some serious server room grade features: a pair of 10G SFP+ cages, 512 MB of RAM, 24 Gigabit Ethernet ports and a sufficient built-in CPU that can handle basic home user needs such as firewall, NAT and even some VPN. And it is extremely affordable – MikroTik is keeping the price on par with the previous generation desktop switches!

Like many other MikroTik switches, CRS326-24G-2S+IN offers the dual boot option that allows you to use either the lightweight SwOS or the advanced RouterOS. The compact and quiet fanless desktop case makes this switch the perfect addition to the best home setups. And it is very easy to transport! But make no mistake – this small switch has all the power and features of its bigger rackmount analogue – the CRS326-24G-2S+RM, nothing has been removed!

CRS326-24G-2S+IN provides all the basic functionality for a managed switch, and even more: port-to-port forwarding, MAC filtering, VLAN configuration, traffic mirroring, bandwidth limitation and even adjust some MAC and IP header fields. SFP+ cage supports both 1.25G SFP and 10G SFP+ modules. Included parts

- 24 V, 1.2 A power adapter
- Product code: CRS326-24G-2S+IN
- CPU: 98DX3236 800 MHz CPU core count: 1
- Size of RAM: 512 MB
- RAM type: DDR3
- Storage: 16 MB, flash

- Number of 1G Ethernet ports: 24
 Number of 10G SFP+ ports: 2
 Operating system: SwOS/RouterOS (dual boot)
 License level: 5
- Supported input voltage: 10 30 V (DC jack); 10 30 V (PoE-in)
- Number of DC inputs: 2 (DC jack, PoE-in)
 Dimensions: 285 x 144 x 44 mm
 Operating temperature: -40°C to +60°C tested
 Max. power consumption: 21 W

Specifications

