

Item no.: 356323

4G+ Cat6 AC1200 WLAN Dual Band Gigabit Router

from **102,74 EUR**

Item no.: 356323
shipping weight: 0.90 kg
Manufacturer: TP-LINK



Product Description

- Advanced 4G+ Router - supports 4G+ Cat6 to boost data speeds up to 300 Mbps*
- Plug in a SIM card and play - no configurations required, compatibility of SIM cards in over 100 countries is ensured through years of field testing
- MU-MIMO supported - simultaneous data streams increase WLAN throughput and network efficiency
- Supports TP-Link OneMesh TM - works with TP-Link OneMesh products to create a flexible and cost-effective mesh network
- Better signal for connections everywhere - enjoy stable and efficient connections to any device thanks to the two external detachable LTE antennas
- Full Gigabit ports - provides reliable wired connections for bandwidth-intensive devices like game consoles and IPTVs
- WLAN router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option when you can't get a 4G connection
- Easy setup and management via the Tether app

HARDWARE FEATURES

- Interface 1 x 10/100/1000 Mbps LAN/WAN port
- 3 x 10/100/1000 Mbps LAN ports
- 1 x Nano SIM card slot
- Dimensions (W*D*H) 202 x 141 x 33.6 mm (7.95 x 5.55 x 1.32 inches)
- Antenna 2 detachable external LTE antennas

WIFI FEATURES

- WLAN standards IEEE 802.11a/n/ac 5 GHz, IEEE 802.11b/g/n 2.4 GHz
- Frequency 2.4 GHz and 5 GHz
- Signal rate 300 Mbps at 2.4 GHz, 867 Mbps at 5 GHz
- Receiver sensitivity 5 GHz: 11a 54M: -77 dBm
- 11ac HT20: -73 dBm
- 11ac HT40: -68 dBm
- 11ac HT80: -64 dBm
- 11n HT20: -77 dBm
- 11n HT40: -73 dBm
- 2.4 GHz: 11g 54M: -74 dBm
- 11n HT20 : -72 dBm
- 11n HT40: -69 dBm
- Transmitting power < 20 dBm (2.4 GHz), < 23 dBm (5 GHz)
- WLAN functions WLAN radio enable/disable, WLAN schedule, WMM, WLAN statistics
- WAN failover Yes
- WLAN security 64/128-bit WEP, WPA/WPA2 Personal, WPA/WPA2 Enterprise
- Network type Compatible with most wireless carriers and supports 4G/3G:
- FDD-LTE: B1/B3/B5/B7/B8/B20/B28
- (2100/1800/850/2600/900/800/700 MHz)
- TDD-LTE: B38/B40/B41
- (2600/2300/2500 MHz)
- DC-HSPA+/HSPA/UMTS: B1/B3/B5/B8
- (2100/850/900 MHz)

SOFTWARE FEATURES

- Quality of service Bandwidth control
- Security DoS, IPv4 SPI firewall, IPv6 firewall, IP and MAC address binding, access control, service filtering
- WAN Type Dynamic IP/Static IP/PPPoE/PPTP (Dual Access)/L2TP (Dual Access)
- Management TP-Link Cloud, Local Management, Remote Management
- DHCP Server, DHCP Client List, Address Reservation
- Port forwarding ALG, virtual server, port triggering, UPnP, DMZ
- Dynamic DNS TP-Link, DynDns, NO-IP
- VPN VPN server: PPTP VPN, OpenVPN
- Parental control URL filtering, time control
- Protocols IPv4, IPv6
- Guest network 2.4 GHz guest network x 1, 5 GHz guest network x 1

OTHER

- Certification CE, RoHS
- Package Contents 4G+ Cat6 300 Mbps LTE AC1200 Wireless Dual Band Gigabit Router Archer MR500
- Power adapter
- RJ45 Ethernet Cable
- Quick Installation Guide
- Environment Operating temperature: 0?~40? (32? ~104?)
- Operating humidity: 10%~90% non-condensing
- Storage humidity: 5%~90% non-condensing

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

