

Item no.: 336570

62958 - Adapter - USB 2.0 Type-A male > 1x serial RS-232 DB9 male

from **28,54 EUR**

Item no.: 336570
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

Delock Adapter - USB 2.0 Type-A male > 1x Serial RS-232 DB9 male, with screws and nuts, ESD protection

This (USB 2.0 to RS-232) adapter by Delock provides a flexible DB9 connection with matching screws and nuts for the operation on serial controllers, printers, measuring instruments, IoT devices, etc. A built-in ESD protection prevents the destruction of the electronic components.

- System requirements: Windows 7/7-64/8.1/8.1-64/10/10-64, Linux Kernel 2.6 and higher; PC or laptop with a free USB type-A port
- Package content: USB 2.0 to 1x serial adapter; 2x screw, driver CD, user manual
- Package: Retail box
- Connectors: 1x USB 2.0 Type-A male, 1x Serial RS-232 DB9 male (serial connector with screws or nuts)
- Chipset: FTDI FT232RL
- Screw type: #4-40 UNC
- Compatibility: USB 3.0, USB 2.0, and USB 1.1 (full speed, 12 Mbps)
- Data transfer rate: Up to 115.2 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: Even, odd, none, mark, space
- Stop bit: 1, 1.5, 2
- Data bit: 5, 6, 7, 8
- Flow control: None, Xon/ Xoff, RTS/ CTS
- FIFO: 128 Byte - TX; 256 Byte - RX
- ESD protection: +/- 15 KV ESD Human Body Model (HBM); +/- 15 KV IEC1000-4-2 air gap discharge; +/- 8 KV IEC1000-4-2 contact discharge
- Current consumption: ca. 150 mA
- Cable length: ca. 35 cm
- Cable incl. connectors: ca. 45 cm
- Operating temperature: 0°C ~ 60°C
- Humidity: 5 ~ 95 %

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

