

Item no.: JVS-ND7004-PD01

JVS-ND7004-PD01 - PoE 4-Channel H.265 4K NVR, for Cameras up to 5 MP

from **97,33 EUR**

Item no.: JVS-ND7004-PD01
shipping weight: 1.10 kg
Manufacturer: Jovision



Product Description

JVS-ND7004-PD01 - PoE 4-Channel H.265 4K NVR, for Cameras up to 5 MP

Jovision 4-channel Network Video Recorder for cameras up to 5 MP. Key Features:

- Adopts the new Vstar GUI, easy to operate
- Supports intelligent coding VSMart, greatly reducing storage space
- Improved compatibility for hard disks, and up to 10 TB
- Supports Intelligent Detection and Human Detection
- Supports face capture, face comparison, and efficient comparison of face information
- Supports face search by face, deduplication, and precise playback
- Supports full PoE camera access, support 4x PoE + 4 non-PoE accesses (a total of 8)

Video and Audio

- IP Camera Input: 4-channel PoE cameras up to 5 MP + 4-channel non-PoE cameras up to 5 MP
- Audio I/O: 1-channel output RCA; Audio output support HDMI

Display

- Interface: 1x HDMI, 1x VGA
- Resolution: HDMI: 3840x2160, 1920x1080, 2560x1440, 1440x900, 1280x1024, 1280x720, 1024x768
- VGA: 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768
- Multi-screen display: Port binding 4; Non-port bonding 1/4/5/6/7/8/9
- OSD: Camera name & time, recording, alarm detecting, remote connection, volume, channel number

Recording

- Compression: H.265/H.264
- Resolution: 6-channel 5.0 MP/4.0 MP/1080P/960P/720P
- Record mode: Manual, schedule, MD

Video Detection and Alarm

- Trigger events: Recording, snapshot, PTZ, voice, e-mail, client, buzzer
- Video detection: Motion detection, no video detection

Playback and Backup

- Sync playback: 2-channel 5.0 MP/3-channel 4.0 MP/4-channel 3.0 MP
- Search mode: Time/date, schedule, motion detection
- Playback function: Day view, hour view, back step, rewind, pause, play, fast forward, slow, step, full screen, snap, sound on/off, zoom
- Backup mode: USB device/network
- USB: 2x USB 2.0

Network

- Interface: 1x RJ-45 port (10/100/1000 Mbps)
- PoE interface: 4-port 100 Mbps IEEE 802.3af PoE
- Network function: TCP/IP, DHCP, UDP, SMTP, NTP
- Smartphone: iPhone, Android
- Interoperability: ONVIF 2.4

Storage

- SATA: 11x SATA interface
- Capacity: Up to 10 TB

General

- Power supply: 52 V DC
- Consumption: ? 50 W (without HDD)
- Working temperature: -10°C ~ 55°C
- Working humidity: 10% ~ 90%
- Dimensions: 260 x 219 x 45 mm
- Weight: ? 1.05 kg (without HDD)

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

