

Item no.: 356466

## 5-Port 10G Multi-Gigabit Switch

from **327,77 EUR**

Item no.: 356466  
shipping weight: 1.60 kg  
Manufacturer: TP-LINK

### Product Description

- Five 10 Gbps ports . 5 x 10 Gigabit ports provide the highest performance of your 10G / Multi-Gig bandwidth and devices, offering up to 100 Gbps switching capacity
- Lightning-fast connections . Provides lightning fast connections to 10G NAS, servers, 10G PCIe adapter / NIC, gaming computers, 2.5G / 5G / 10G WiFi 6 AP, 8K video and more
- Ideal for various scenarios . Designed for lightning fast connections in LAN parties, home entertainment, small and home offices and workstations
- Optimal 5-speed connections . Auto-negotiation of 5-speed connections (100 Mbps / 1G / 2.5G / 5G / 10G) provides optimal performance
- Quiet operation . Revolutionary fanless design provides unprecedented silent operation, ideal for any home or business
- Rugged Metal Enclosure . The rugged metal chassis, desktop / wall mount and professional heat dissipation design are well suited for various environments
- Plug and Play . Enables easy deployment without the need for a technician

#### HARDWARE FEATURES

- Standards and protocols IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1p, 802.3an, 802.3bz
- Interface 5x 100 Mbit/s/1 Gbit/s/2.5 Gbit/s/5 Gbit/s/10 Gbit/s ports, auto-negotiation, auto-MDI/MDIX
- Number of fans Fanless
- External power supply External power supply unit (output: 12 VDC / 2.0 A)
- LEDs
- System power: 1
- Link/Act indicators: 5, 1 indicator per port, integrated in each RJ-45 port
- Dimensions (W\*D\*H) 8.9 x 5.2 x 1.4 inches (226 x 131 x 35 mm)
- Maximum power consumption 21.4 W

#### POWER

- Switching capacity 100 Gbps
- Packet forwarding rate 74.4 Mpps
- MAC address table 32 K
- Packet buffer memory 2 MB
- Jumbo frames 10 KB

#### SOFTWARE FEATURES

- Advanced functions
- 802.3X flow control
- 802.1p/DSCP QoS
- Transfer method Store and forward

#### OTHER

- Certification CE, FCC, RoHS
- Package contents: 5-Port 10G Multi-Gigabit Desktop/Rackmount Switch TL-SX105; Power cord; Installation guide; Rubber feet
- Operating temperature: 0-40 °C (32-104 °F)
- Storage temperature: -40-70 °C (-40-158 °F)
- Operating humidity: 10-90 % relative humidity, non-condensing
- Storage humidity: 5-90 % relative humidity, non-condensing

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

