

Item no.: 339064

42638 - External USB Type-C(TM) Combo Metal Enclosure for M.2 NVMe PCIe or SATA SSD - tool free

53,64 EUR

Item no.: 339064
shipping weight: 0.10 kg
Manufacturer: Delock

**M.2 NVMe
SATA**



Product Description

Delock External USB Type-C(TM) Combo Enclosure for M.2 NVMe PCIe or SATA SSD - tool free

This enclosure by Delock enables the installation of an M.2 PCIe NVMe SSD or SATA M.2 SSD in 2280, 2260 and 2242 format. It can be connected via USB to the PC or laptop. The robust metal housing with cooling fins ensures an optimum temperature of the memory.

The big advantage of this Delock M.2 enclosure is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the enclosure. The memory is automatically recognized by the chipset and can then be used.

The special feature of this enclosure is that no tools are required to install the M.2 SSD. The lid is pushed backwards and the SSD is plugged into the slot, pressed down until it locks into place at the corresponding snap nose. Then the lid is reattached until it locks.

- Connectors external: 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C(TM) female
- Connectors internal: 1 x 67 pin M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Bootable
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing
- Dimensions (LxWxH): ca. 1117 x 40 x 13 mm
- Hot Plug, Plug & Play
- System requirements: Android 9.0 or above, Chrome OS 78.0 or above, Linux Kernel 4.6.4 or above, Mac OS 10.15.3 or above, Windows 8.1/8.1-64/10/10-64, PC or laptop with a free USB Type-C(TM) port, PC or laptop with a free Thunderbolt(TM) 3 port
- Package content: External enclosure M.2, cable USB-C(TM) male to USB-C(TM) male, length ca. 30 cm, cable USB-C(TM) male to USB Type-A male, length ca. 30 cm, 2 x thermal conductive pad, 1 x thermal conductive plate, user manual

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

