


Item no.: 342491

95245 - Module MiniPCIe I/O PCIe full size 2x serial RS-422/485 with 600 W Surge

from **74,46 EUR**

Item no.: 342491
shipping weight: 0.20 kg
Manufacturer: Delock



Product Description

Module MiniPCIe I/O PCIe full size 2x serial RS-422/485 with 600 W Surge

This MiniPCIe adapter by Delock expands your system by two additional serial ports, which you can lead out through the slot bracket. You can connect different serial devices to this adapter.

Package content

- MiniPCIe module
- 2x serial connection cable (pin header to DB9)
- 2x terminal block adapter
- 1x standart slot bracket with two DB9 ports
- 2x low profile slot bracket with one DB9 ports
- Driver CD
- User manual

- Connector: On the module: 2x 10-pin pin header male; On the slot bracket (1x standard): 2x serial RS-422/485 DB9 male with screw nuts; On slot bracket (2x low profile): 1x serial RS-422/485 DB9 male with screw nuts
- Chipset: Exar XR17V352
- Form factor: miniPCIe full size
- Interface: PCI Express revision 2.0
- Data transfer rate up to 921.6 Kb/s
- Compatible with 16C550 UART
- 600 W surge
- Cable length: ca. 30 cm (incl. connector)

System requirements

- Windows Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64, Linux Kernel 2.6
- Mainboard with a free miniPCIe slot with a PCIe interface

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

