

Item no.: 343564

WH67 UC - DECT Wireless Convertible Headset

191,59 EUR

Item no.: 343564
shipping weight: 1.10 kg
Manufacturer: Yealink



Product Description

WH67 UC - DECT Wireless Convertible Headset

The Yealink WH67 is an industry-leading convertible DECT wireless headset, opening an entirely new form of desktop collaboration. It works seamlessly with major UC platforms and integrates natively with Yealink IP phones. The 4.0 inch (480 x 800) capacitive touch screen of the base offers a new work experience as you have full control just by one touch. It acts as a workstation, managing phone calls, connecting with multiple devices (desk phone/mobile phone/computer), charging mobile phone wirelessly, and even playing a speakerphone's role. Best of all, deploying such a multifunctional workstation only needs to direct plugging. The easiest things to do, the greatest convenience to enjoy.

- 4.0 inch (480 x 800) capacitive touch screen
- 2x feature buttons
- 1x type-A USB 3.0 port
- Built-in Bluetooth 4.2
- Connectivity: USB 3.0 & 2x Bluetooth devices
- Integrated busylight LED indicator
- Built-in hub: 2x type-A USB 3.0 ports
- Charging stand (for headset)

Battery

- Talk time: up to 8 hours
- Standby time: 54 hours
- Charging time: 2.5 hours (12 V/2 A)

DECT

- Wireless range: up to 120 m/394 feet
- Secure DECT (level): Step C: Authentication – DSAA2, encryption – DSC2 (128 bit)
- Cordless Advanced Technology: CAT-iq 2.0

Audio (Headset)

- Microphone type: Dual microphone
- Microphone sensitivity: -38,0+/-2 dBV
- Microphone frequency range: 100 Hz-10 kHz
- Speaker size: ? 13.6
- Speaker sensitivity: 116+/-3 dB, 0.179 V
- Speaker impedance: 32+/-4.8 ?
- Speaker max. output power: 10 mW
- Speaker frequency range: 20 Hz - 14 kHz
- Speaker bandwidth - talk mode: Wideband, 100 Hz - 8 kHz
- Speaker bandwidth - music mode: Super wideband, 20 Hz - 14 kHz (pending)
- Hearing protection: Peak Block Protection (EN50332), Australian G616 Protection (AU G616), Daily Noise Exposure Protection

Audio (Base)

- Microphone type: ECM omnidirectional microphone
- Microphone sensitivity: -38.0+/-2 dBV
- Microphone frequency range: 70 Hz - 20 kHz
- Speaker size: 40 x 20.8 mm
- Speaker sensitivity: 97+/-3 dB
- Speaker impedance: 4 ?+/-15%
- Speaker max. output power: 4 W
- Speaker frequency range: 160 Hz - 20 kHz

Easy Call Management

- Answer/end/reject a call
- Volume up/down
- Microphone mute

Package Features

- Package contents: Base, headset, earhook & eartips, headband, neckband, power adapter, 2x 1 m USB 3.0 cable, quick start guide
- Optional accessories: Busylight BLT60, wireless charger, Bluetooth dongle BT50
- Carton measurements: 594 x 434 x 275 mm

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

