

Item no.: 344210

VP1600EILCD - 1600 VA / 960 W GreenPower UPS Line-Interactive, 8x IEC C13

216,51 EUR

Item no.: 344210
 shipping weight: 11.40 kg
 Manufacturer: CyberPower



Product Description

1600 VA / 960 W GreenPower UPS Line-Interactive, 8x IEC C13

CyberPower VP1600EILCD offers office and home office users a reliable battery backup and protects PCs and other electronic devices from surges, voltage peaks, power failures and other power disturbances. Developed with GreenPower UPS™ technology to improve operational efficiency and minimize energy consumption, users can achieve significant energy cost savings compared to conventional UPS systems. The UPS offers automatic voltage regulation (AVR) to supply connected devices in a secure voltage range.

The UPS has a multifunctional LCD display to clearly show the power and battery status. The product has data line protection for telephones, network and communication devices against overvoltages / peaks and this without suppression up to a speed of 1 GB. For easy configuration, unattended shutdown and real-time monitoring, the UPS is compatible with the PowerPanel® UPS management software.

General

- Phase: Single phase
- Form factor: Tower
- UPS topology: Line-interactive
- Energy saving technology: GreenPower UPS™ bypass technology

Input

- Nominal input voltage (Vac): 230 ± 10%
- Input voltage range (Vac): 167 ~ 295
- Input frequency (Hz): 50 ± 5; 60 ± 5
- Input frequency detection: Auto detection
- Nominal input current (A): 6.96
- Type of input connector: IEC C14

Output

- Output (VA): 1600
- Power (watt): 960
- Battery waveform: Simulated sine wave
- Output voltage (Vac): 230 ± 10%
- Battery Frequency (Hz): 50 ± 1%; 60 ± 1%
- Automatic Voltage Regulation (AVR): Simple Boost, Simple Buck
- Overload protection: Automatic circuit breaker
- Outlets - total: 8
- Outlets: IEC C13 x 8
- Outlets, battery backup & surge protection: 4
- Outlets - only surge protection: 4
- Typical transmission time (ms): 4

Battery

- Runtime at half load (min.): 11
- Runtime at full load (min.): 2
- Typical charging time (hours): 8
- Battery start: Yes
- User replaceable: Yes - Qualified personnel only
- Battery type: Maintenance-free lead gel

Overvoltage protection & Filter

- Overvoltage suppression (Joule): 450
- EMI / RFI filtering: Yes
- Telephone / modem / network protection RJ11 / RJ45 (combi): 1-on, 1-off

Management & Communication

- LCD panel: Yes
- LCD information display: Operating mode, power display, battery status, load status, error and warning, further information
- LCD setting & Control: Mode setting, alarm setting, input and output, battery setting, error and warning
- LED displays: Operating status
- HID compatible USB port (s): 1
- Audible alarms: Battery mode, low battery, overload, UPS failure
- Management cable (pc.): 1x USB cable
- Ethernet data transfer speed: Up to 1 Gbps
- Energy management software: PowerPanel® Personal (recommended)

Physical

- Enclosure construction: Plastic
- Color: Black

Physical size - UPS unit

- Dimensions (WxHxD, inches): 3.9 x 11 x 14
- Dimensions (WxHxD, mm.): 100 x 281 x 355
- Weight (lbs.): 22.97
- Weight (kg.): 10.42

Environment

- Operating temperature (° C): 0 ~ 40
- Relative humidity during operation (non-condensing,%): 0 ~ 90
- Operating Altitude (feet / meters): 0-9,843 feet (0-3,000 meters)
- Storage temperature (° F): -4 ~ 122
- Storage temperature (° C): -20 ~ 50
- Storage relative humidity (non-condensing): 0 ~ 90
- Storage height (feet / meters): 0-9,843 feet (0-3,000 meters)
- Online heat dissipation (BTU / h): 68
- Audible noise at 1 m from the unit (dBA): 50

Certifications

- Certifications: CE, EAC
- RoHS: Yes

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

