

Item no.: 344183

## PR750ELCDGR - Line-Interactive 750 VA/675 W Pure Sine Wave UPS

from **402,74 EUR**

Item no.: 344183  
 shipping weight: 13.50 kg  
 Manufacturer: CyberPower



### Product Description

#### PR750ELCDGR - Line-Interactive 750 VA/675 W Pure Sine Wave UPS

CyberPower PR750ELCDGR Line-Interactive UPS with seamless Pure Sine Wave provides the best power protection available for office system devices including PCs, workstations, networking devices, and peripherals. It's typically integrated in the back office, server room, and data center environment.

The UPS can be locally managed via USB or serial ports, or remotely managed via an SNMP card (an optional Remote Management Card), allowing administrators and users unsurpassed flexibility to remotely access each UPS through the network to perform real-time monitoring, UPS configurations, and scheduled system shutdowns by using PowerPanel Management software. The product is also certified to be interoperable and compatible with Cisco, which helps to achieve the best energy performance possible.

#### General

- Phase: Single phase
- Form factor: Tower
- UPS topology: Line-interactive
- Energy saving technology: GreenPower UPS™ Bypass Technology
- Energy Star qualified: Yes
- Active PFC compatibility: Yes

#### Input

- Nominal input voltage (Vac): 230
- Input voltage range (Vac): 150 ~ 301
- Input frequency (Hz): 60 ± 3, 50 ± 3
- Input frequency detection: Auto-sensing
- Input connector type: IEC C14

#### Output

- Capacity (VA): 750
- Capacity (Watts): 675
- On battery waveform: Pure sine wave
- On battery voltage (Vac): 230 ± 5%
- On battery frequency (Hz): 60 ± 1%, 50 ± 1%
- Power factor: 0.9
- Automatic voltage regulation (AVR): Double boost, single buck
- Overload protection: Internal current limiting
- Outlets, total: 4
- Outlet type: 2x IEC C13, 2x Schuko
- Outlets, battery & surge protected: 4
- Typical transfer time (ms): 4

#### Battery

- Runtime at half load (min.): 10.5
- Runtime at full load (min.): 2.5
- Typical recharge time (hours): 8
- Quick recharge time (hours): 3
- Start on battery: Yes
- User-replaceable: Yes
- Hot-swappable: Yes
- Battery type: Sealed lead-acid
- Replacement battery pack: RBP0014
- RBP quantity (pcs.): 1

#### Surge Protection & Filtering

- Surge suppression (Joules): 405
- EMI/RFI filtration: Yes

#### Management & Communication

- LCD panel: Yes
- LCD types: Detachable LCD panel
- LCD information display: Operation type, power status, battery status, load status, fault & warning, other information
- LCD setting & control: Mode setting, alarm setting, input & output, battery setting, fault & warning, event & log
- LED indicators: Power on, line mode, battery mode, wiring fault, replace battery
- HID compliant USB port(s): 1
- Emergency Power Off (EPO) port: Yes
- Audible alarms: Battery mode, low battery, overload, UPS fault
- Management cable (pcs.): 2x power cord, 1x USB cable, 1x EPO cable
- Power management software: PowerPanel® Business (recommended)
- SNMP/HTTP remote monitoring: Yes, with optional RMCARD205

#### Physical

- Enclosure construction: Metal
- Color: Black

#### Physical Size - UPS Module

- Dimensions (W x H x D, in.): 5.4 x 6.4 x 13.7
- Dimensions (W x H x D, mm.): 136 x 162 x 349
- Weight (lbs.): 27.1
- Weight (kg.): 12.3

#### Environmental

- Operating temperature (°F): 32 ~ 104
- Operating temperature (°C): 0 ~ 40
- Operating relative humidity (non-condensing, %): 0 ~ 95
- Operating elevation (feet/meters): 0-9,843 feet (0-3,000 meters)
- Storage temperature (°F): 5 ~ 113
- Storage temperature (°C): -15 ~ 45
- Storage relative humidity (non-condensing, %): 0 ~ 95
- Storage elevation (feet/meters): 0-49,213 feet (0-15,000 meters)
- Online thermal dissipation (BTU/hr): 75

#### Certifications

- Certifications: CE
- RoHS: Yes

## Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

