

Item no.: 344121

B0620SC0-DE - 6-Way Socket Strip with Surge Protection

from **22,19 EUR**

Item no.: 344121
shipping weight: 0.50 kg
Manufacturer: CyberPower



Product Description

6-Way Socket Strip with Surge Protection

CyberPower B0620SC0-DE is ideal for home surge protection. The surge protector is designed with Metal Oxide Varistor (MOV) technology to safeguard the surge suppressor and connected electronic equipment by absorbing spikes in energy caused by storms and electrical power surges. The product also features overload protection, impact-resistant casing and more, providing reliable protection for your electronic devices.

Input

- Input voltage range (Vac): 200 ~ 250
- Input frequency (Hz): 50/60
- Maximum input current (A): 10
- Input connector type: Schuko
- Plug style: Right angle
- Power cord length (ft.): 6
- Power cord length (m.): 1.8
- Power on/off switch: Yes

Output

- Output voltage (V): Depends on input
- Overload protection: Circuit breaker
- Overcurrent protection (A): 10
- Outlet(s), total: 6
- Outlet type: 6x Schuko
- Outlet(s), widely spaced: 0
- Outlet(s), ECO controlled outlets: 0

Surge Protection & Filtering

- Surge suppression (Joules): 350
- Maximum surge voltage (V): 6000
- Maximum surge current (A): 7500
- Maximum surge current (L-N, L-G, N-G; A): Line to Neutral (L-N): 7500
- Clamping voltage (L-N, L-G, N-G; V): Line to Neutral (L-N): 1200
- Response time (ns): <1
- Attenuation (dB): Up to 0 dB

LED Indicators

- LED indicators: Surge protected

Physical

- Form factor: Strip
- Enclosure fire-resistance: Yes
- Color: Black
- Keyhole mounting slots: Yes
- Safety shutter: Yes

Physical Size

- Dimensions (WxHxD, in.): 1.93 x 12.08 x 1.63
- Dimensions (WxHxD, mm.): 49 x 325 x 41.5
- Weight (lbs.): 0.72
- Weight (kg.): 0.375

Environmental

- Operating temperature (°F): 32 ~ 95
- Operating temperature (°C): 0 ~ 35
- Operating relative humidity (non-condensing, %): 0 ~ 95
- Operating elevation (feet/meters): 0-9,843 feet (0 - 3,000 meters)
- Storage temperature (°F): 5 ~ 113
- Storage temperature (°C): -15 ~ 45
- Storage relative humidity (non-condensing, %): 0 ~ 95
- Storage elevation (feet/meters): 0 - 49,213 feet (0-15,000 meters)

Certifications

- Certifications: CE
- RoHS: Yes

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

