

Item no.: CAP-XL-AC

RBCAPGI-5ACD2ND-XL - cAP XL ac, 2.4/5 GHz ceiling AP

from **89,25 EUR**

Item no.: CAP-XL-AC
shipping weight: 0.50 kg
Manufacturer: MikroTik



Product Description

RBCAPGI-5ACD2ND-XL - cAP XL ac, 2.4/5 GHz ceiling AP

Need a nice-looking access point that won't get in your way? Or perhaps you're managing the network in a crowded place and don't want everyone to have physical access to the device? Either way – ceiling is the answer! The device itself is pretty sleek - the low profile attracts less attention than a smoke detector. Your clients, guests, or colleagues won't even notice it. But they will definitely notice the blazing fast wireless connection all across the premises.

The new design features a larger high-gain antenna, higher sensitivity, and a built-in reflector. These improvements allow increasing the covered area by up to 100%, compared to the previous cAP models!

The dual-band, dual-chain 2.4 and 5 GHz wireless radio provides a strong coverage in 360 degrees around it, so you don't have to worry about the placement of the device so much. Putting it on the ceiling eliminates many signal absorption problems, such as the signal being blocked by large TV sets, metal cubicle walls in open space offices, etc.

Even though the radio supports repeater mode, the two Gigabit Ethernet ports give you the ability to extend your network with cables, even if PoE power is required: the cAP XL ac supports 802.3af/at PoE input on the first port and passive PoE output (up to 57 V) on the second port.

Included parts

- 24 V/1.2 A power adapter
- Ceiling mount
- Gigabit PoE injector
- Fastening set

Specifications

- Product code: RBCAPGI-5acD2nD-XL
- CPU: Quad core IPQ-4018 710 MHz
- Size of RAM: 128 MB
- RAM type: DDR3L
- Storage: 16 MB, Flash
- Number of 1G Ethernet ports: 2
- Wireless: 2.4 GHz; 5 GHz
- Supported protocol: 802.11b/g/n; 802.11a/n/ac
- Antenna gain: 6 dBi; 5.5 dBi
- Number of chains: 2
- Operating system: RouterOS (license level 4)
- Switch chip model: IPQ-4018
- Dimensions: 191 x 42 mm
- Operating temperature: -40°C to +70°C tested

Powering

- PoE-in: 802.3af/at
- PoE-out: Passive PoE up to 57 V
- Smart PoE: Injector
- Number of DC inputs: 1
- PoE-out ports: Ether2
- Supported input voltage: 17-57 V
- Power adapter nominal voltage: 24 V
- Power adapter nominal current: 1.2 A
- Max. power consumption (without attachments): 11 W
- Max. power consumption: 24 W

Certification & Approvals

- Certification: CE, FCC, IC

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

