

Item no.: 345834

MS101 - HiFi DAC HAT for Raspberry Pi

from **45,54 EUR**

Item no.: 345834
shipping weight: 0.10 kg
Manufacturer: 52Pi



Product Description

HiFi DAC HAT for Raspberry Pi

The 52Pi HiFi DAC HAT is the best optimized partner for RPi audio output. It uses on-board PCM5122 as the IIS clock master instead of the clock from the RPi which comes with too much jitter. It adds dual low jitter oscillators to support a more exact sample rate clock. It does not require soldering nor additional cables, just plug it in and do some simple configuration.

- Compatible with Raspberry Pi Zero, Zero W, 3B, 3B+ with 40-pin connector
- Connects directly to the Raspberry Pi board, no additional cables required, no soldering
- Easy to get more beautiful and fantastic sound by this RPi+DAC HiFi suit
- Absolutely perfect to support all Raspberry Pi music playback systems, such as OSMC, Max2Play, RuneAudio, Volumio, Moode, PiCorePlayer, PiMusicBox, OpenELEC, Raspbian, Ubuntu etc.
- Supports playing music from a hard disk or over the network
- Supports DSD over PCM (DOP) mode
- Class-leading stereo audio DAC PCM5122, sample rates up to 384-kHz/32-Bit
- Paired with stereo high fidelity headphone amplifier TPA6133
- Provides 2.1 Vrms ground-centered outputs coupled with film capacitor
- On-board a pair of gold plated RCA (Left & Right) jacks and a 3.5 mm high-end headphone jack output, allowing you to freely play your music through Raspberry Pi to another terminal
- Comes with software, documentation and technology support
- On-board EEPROM and infrared receiver extended functions (no soldering by default)

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

