

Item no.: CCR2116-12G-4S+

CCR2116-12G-4S+ - Cloud Core Router with 16 GB RAM, 4x SFP+ Cages, 13x Gbit LAN

from **856,96 EUR**

Item no.: CCR2116-12G-4S+
shipping weight: 1.60 kg
Manufacturer: MikroTik



Product Description

Cloud Core Router 2116-12G-4S+ with 16 GB RAM, 4x SFP+ Cages, 13x Gbit LAN

MikroTik wanted to see the full potential of the good, old, reliable 10G networking combined with a modern CPU. CCR2116-12G-4S+ allows you to forget about CPU limitations in your setup. Like its younger brother – the amazing CCR2004, this router features the mighty Amazon Annapurna Labs Alpine CPU.

But with 16 cores running at 2 GHz, this CCR eats the other one for breakfast. For example, MikroTik see at least a 15% increase in single-core performance. And that is the most important aspect when it comes to heavy operations based on per-connection processing. Like queues, for example. CCR2116-12G-4S+ sets a new standard of single-core performance in the whole CCR product family! And it supports Layer 3 Hardware Offloading!

Obviously, you need the right connectivity to harness this power. There are four 10G SFP+ ports. They have a separate, full-duplex line connected to the Marvell Aldrin family switch chip. Then there are Gigabit Ethernet ports. 12 of them are running through the Marvel chip. And there is another Gigabit port connected directly to the CPU. For management purposes.

Each group of 4 ports has a separate full-duplex connection to the switch chip. No bottlenecks here. You can expect switch-like throughput in most setups. The new generation of processors offers mind-blowing performance. If you look at the CCR1036 - the powerhouse with a 36 core CPU, the new CCR2116 can easily double the performance. 16 cores vs 36 cores. Double the performance. Or even more.

If you are a rather large ISP, dealing with dynamic routing, massive BGPs, complex firewall rules, and intricate quality of service configurations... this is the right device for you. Combination of raw power and utility with the reliable 10G networking. And yes, like with any ISP-level device, MikroTik have included a dual-redundant power supply. So you have one less thing to worry about.

CCR2116-12G-4S+: technology tested by time, built for the future.

Parts included

- 2x IEC cables
- Rackmount bracket white
- K-57 kit
- Product code: CCR2116-12G-4S+
- CPU: AL73400 2 GHz
- CPU architecture: ARM 64-bit
- CPU core count: 16
- RAM size: 16 GB
- RAM type: DDR4
- Memory: 128 MB, NAND
- Number of 1G Ethernet ports: 13
- Number of 10G SFP+ ports: 4
- Number of M.2 slots: 1
- Operating system: RouterOS (licence level 6)
- Switch chip model: 98DX3255
- Dimensions: 443 x 199 x 44 mm
- Operating temperature: -20°C to +60°C

Power supply

- Number of AC inputs: 2
- AC input range: 100-240 V
- Rated voltage power supply unit: 12 V
- Rated current power supply unit: 10.8 A
- Max. power consumption (without attachments): 60 W
- Max. power consumption Power consumption: 72 W

Certification & Approvals

- Certification CE, FCC, IC

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

