

Item no.: CRS310-1G-5S-4S+IN

## CRS310-1G-5S-4S+IN - Cloud Router Switch CRS310

from **171,17 EUR**

Item no.: CRS310-1G-5S-4S+IN

shipping weight: 0.70 kg

Manufacturer: MikroTik



### Product Description

#### CRS310-1G-5S-4S+IN - Cloud Router Switch CRS310

This switch is an indoor variation of the prominent netFiber 9 switch – used by many small and medium ISPs for reliable 10 Gigabit fibre connections stretching over a 100 meters. With five 1G SFP ports, four 10G SFP+ ports, and an additional Gigabit Ethernet port, this is the perfect upgrade for existing CRS212 setups. You're getting the modern ARM v7 CPU, 256 MB of RAM, and better cooling. The new Marvell switch-chips bring phenomenal performance to the table!

The Gigabit Ethernet port has a direct connection to the switch chip – so you can enjoy full Gigabit speed there. And it supports PoE-in, giving you an additional powering option in tricky spots.

CRS310-1G-5S-4S+IN is a fantastic tool for anyone working with indoor connections over 100 meters while keeping data loss and ping low. Optical fiber can be a great alternative to copper if you are worried about electromagnetic interference, tampering or eavesdropping.

- Product code: CRS310-1G-5S-4S+IN
- CPU: 98DX226S 800 MHz
- CPU architecture: ARM 32-bit
- CPU core count: 1
- Size of RAM: 256 MB
- RAM type: DDR3
- Storage: 16 MB, Flash
- Number of 1G Ethernet ports: 1
- Number of 1G SFP ports: 5
- Number of 10G SFP+ ports: 4
- Switch chip model: 98DX226S
- Dimensions: 200 x 166 x 45 mm
- Operating system: RouterOS, license level 5
- Operating temperature: -40°C to +70°C
- Number of DC inputs: 2 (PoE-in, DC jack)
- PoE-in input voltage: 18-57 V
- DC jack input voltage: 18-57 V
- Power adapter nominal voltage: 24 V
- Power adapter nominal current: 1.2 A
- Max. power consumption without attachments: 8 W
- Max. power consumption: 20 W
- Included parts: 24 V 1.2 A power adapter, fastening set, rack ears

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

