

Item no.: 351677

PPEX00000060 - iButton reader, compatible with iButton keys (magnetic/non-magnetic)

12,^{48 EUR}

shipping weight: 0.10 kg Manufacturer: Teltonika



Product Description

iButton reader, compatible with iButton keys (magnetic/non-magnetic)

One of the implemented features for fleet management devices is the 1-Wire data protocol, which enables the connection of iButton. The iButton device is perfect for any application where AVL data needs to travel along with a person or object identification.

iButton is a fleet management tracking solution in the following cases:

- Driver authorization gives ability to use vehicle only for specific iButton owners and identify which driver is on the road.
 Immobilizer without iButton authorization you can not run engine starter and use vehicle.
 Auto Geofencing gives ability to know when car leaves customized areas without iButton authorization.

- Interface: White wire 1-Wire signal, brown wire ground
 Case material: Plastic (polyacetal)
 Ring material: Ferrite steel with chrome plating
 Signal joint material: Brass with chrome plating
 Wire dimensions: 2 wires Ø 0,25 mm2, 40 cm length
 Fastening method: M12 screw, tape, glue, etc.
 Operating temperature: From -40°C to +85°C

- Operating humidity: Up to 70% Supported 1-Wire commands: 0x33 (0x0F) Read ROM, 0xF0 Search ROM
- Regulatory: RoHS certified

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

