

Item no.: 352490

## PR1KCL28 - Combo Quad Mobile/GNSS Roof SMA Antenna

**41,48 EUR**

Item no.: 352490  
shipping weight: 0.50 kg  
Manufacturer: Teltonika



### Product Description

PR1KCL28 - Combo Quad Mobile/GNSS Roof SMA Antenna

Combo mobile/GNSS antenna for use with RUTX12 and RUTX14.

GNSS Antenna

- Frequency range: 1575.42 MHz
- Polarization: RHCP
- Impedance: 50  $\Omega$
- LNA gain: 28 $\pm$ 2 dB
- Supply voltage: 3-5 V DC
- Current consumption: < 15 mA
- V.S.W.R: <2.0
- Connector: SMA male
- Cable: 1x RG174, 3000 mm

LTE MIMO Antenna

- Frequency range: 698-960 / 1710-2690 MHz
- Polarization: Linear
- Impedance: 50  $\Omega$
- Gain: 3 dBi
- V.S.W.R: <3.0
- Impedance: 50  $\Omega$
- Connector: SMA male
- Cable: 4x RG174, 3000 mm

Mechanical / Environmental

- Radome material: ABS
- Radome ingress protection rating: IP67
- Mounting method: Screw
- Operating temperature: -40°C to +85°C
- Operating relative humidity: < 95 %
- RoHS compliant: Yes
- Weight: 540 g

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



