

Item no.: 357385

62784 - HDMI Audio Extractor 4K 30 Hz compact

from **27,61 EUR**

Item no.: 357385
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

Description This adapter by Delock can be used to decouple the audio signal from an HDMI transmission. While the image signal is displayed on a TV or monitor, the audio signal can be output digitally (S/PDIF) or analogue (stereo) to other devices, such as headphones or surround receivers. Technical data- Connections: Input: 1 x HDMI-A 19 pin plug 1 x USB type Micro-B socket (5 V power supply) Output: 1 x HDMI-A 19 pin socket 1 x 3.5 mm 3 pin jack socket (audio) 1 x TOSLINK socket S/PDIF- High Speed HDMI, 3D and HDCP 1.4 Automatic switching to stereo (2.0) when using the jack socket and automatic muting of the digital output- Resolution up to 3840 x 2160 @ 30 Hz (8-bit), 1920 x 1080 @ 60 Hz (12-bit)- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s maximum- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio Supported sampling rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)- HDMI audio is passed through to the output (pass-through)- Power consumption: max. 2 W max. System requirements- One free HDMI-A socket- One free USB Type-A socket Package contents- HDMI Audio Extractor- USB Type-A to Type Micro-B cable, length approx. 15 cm- Operating instructions

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

