

Item no.: 357821 LTE antenna MHF® I connector 0.5 - 2.0 dBi 1.13 15 cm PCB internal adhesive mounting



shipping weight: 0.10 kg Manufacturer: Delock



## Product Description

This LTE antenna can be connected to a device with MHF® I connector to receive and transmit signals.

- Connection: 1 x MHF® I plug
  Frequency range:791 960 MHz1710 2170 MHz2500 2700 MHz
  GSM, UMTS, LTE, ZigBee, DECT, Z-Wave, NB-IoT, WLAN, Bluetooth, LoRa
  Antenna gain: 0.5 2.0 dBi
  Impedance: 50 Ohm
  Mounting type: adhesive mounting
  Operating temperature: -10 °C ~ 55 °C
  Cable type: capital

- Operating temperature: -10 °C ~ 55 °C
  Cable type: coaxial
  Cable type: 1.13
  Cable colour: black
  Cable diameter: approx. 1.13 mm
  Cable attenuation: 3.2 dB @ 2.4 GHz per metre
  Smallest bending radius: approx. 4.5 mm
  Dimensions (LxWxH): approx. 85.0 x 17.0 x 0.8 mm

System requirements

• Device with a free MHF® I connection

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

