

Item no.: 355322

8060-HS050W - Patchcable Cat.6a, U/FTP, 5m, white

from **10,36 EUR**

Item no.: 355322
shipping weight: 0.10 kg
Manufacturer: VARIA Group



Product Description

The flexible, thin and halogen-free SlimLine Cat. 6A patch cable with effective latching nose protection (RNS®) is up to 10 Gigabit-capable and therefore suitable for all network connections. Connect your PC, TV, notebook, game console and many other network-compatible devices to the Internet or your network without any problems, even in hard-to-reach places.

Thanks to the slim design and a small diameter of approx. 4 mm, these SlimLine patch cables can be laid quickly and easily between skirting boards or in the wall termination strip. Even in areas where many cables come together, these cables score with their high packing and bundle density. In addition, the air flow and cooling performance can be improved in server cabinets, for example, due to the smaller space requirement.

The conductors of this patch cable are made of copper (CU) and the cores are shielded. This high-quality cable construction enables optimal signal transmission and higher break resistance of the cable. For perfect signal transmission, the RJ45 plugs are shielded and equipped with gold-plated copper contacts.

The snap-in lug protection prevents the snap-in lug on the patch cable plug from bending away. This makes broken lugs a thing of the past!

The U/FTP shielding (PiMF) of the cable and the shielded RJ45 plugs ensure a consistently high and loss-free signal transmission.

Compared to PVC cables, the Low Smoke Zero Halogen (LSZH) cable sheath causes only very low levels of toxic smoke gases and smoke development in the event of a fire. This makes the cables ideal for indoor installation - they are mandatory in public areas.

The Cat. 6A SlimLine patch cables are downward compatible with Cat. 6 and Cat. 5e. This means they can be integrated into existing installations without any problems.

- Cat. 6A patch cable, downward compatible with Cat. 6 and Cat. 5e
- Suitable for 10/100/1000/10000 Base-T Ethernet networks (10 Gigabit capable)
- Max. Bandwidth: 500 MHz
- Shielded RJ45 plugs (8P8C) on both sides with latching nose protection (RNS®)
- Plug with gold-plated contacts
- Assignment 1:1 according to EIA/TIA-568B
- S/FTP cable (shielding foil + braiding)
- PiMF (cores in pairs in metal foil)
- Inner conductor: AWG 32/7
- Conductor material and contacts made of copper (CU)
- Cable sheath material: LSZH
- Outer sheath diameter: 4.0mm +/- 0.2 mm
- Flame retardant according to IEC 60332-1
- Halogen-free according to IEC 60754-2
- Low smoke according to IEC 61034
- Suitable for connecting various devices: e.g. patch panels, switches, routers, modems with RJ45 connection, etc
- Colour: white
- Length: 5 m

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

