

Item no.: 357825

GSM/UMTS antenna SMA St. 0.7 - 1.6 dBi 1 m ULA100 omni rigid outdoor white

42,27 EUR

Item no.: 357825
shipping weight: 0.10 kg
Manufacturer: Delock

Product Description

This GSM/UMTS/LTE antenna can be connected to a GSM/UMTS/LTE device with SMA connector to receive and transmit signals.

- Connectors: SMA connector
- Frequency range: 824 - 960 MHz, 1710 MHz - 2170 MHz
- Antenna gain: 0.7 dBi @ 824 - 960 MHz, 1.6 dBi @ 1710 MHz - 2170 MHz
- Impedance: 50 Ohm
- Polarisation: Linear, vertical
- Horizontal coverage angle: 360
- VSWR: 4.0 @ 824 - 960 MHz, 2.5 @ 1710 MHz - 2170 MHz
- Operating temperature: -10°C ~ 50°C
- Housing material: Polycarbonate
- IP67 protection class
- Screw mounting with 13 mm hole
- Colour: White
- Dimensions (LxD): approx. 77 x 45 mm
- Cable type: Coaxial
- Cable type: ULA 100
- Cable colour: Black
- Cable attenuation: 1.4 dB @ 2500 MHz per metre
- Cable diameter: approx. 2.79 mm
- Cable length: approx. 1 m

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

