

Item no.: 361695

USB 2.0 to serial TTL converter with 6 single pin sockets 1.8 m (5 V)

from **16,73 EUR**

Item no.: 361695
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

This USB 2.0 to TTL converter from Delock can be connected directly to GPIO (General Purpose Input/Output) connectors or UART (Universal Asynchronous Receiver/Transmitter) interfaces. The converter is suitable for applications on single-board computers, controllers, FPGAs, MCUs and in circuit electronics, etc.

- Connections: 1x USB 2.0 type-A plug > 1x TTL 5 V 6-pin pin jacks single
- Chipset: FTDI FT232RL
- Wire gauge: 26 AWG
- No-load current: 70 μ A
- Compatible with UHCI/OHCI/EHCI controller
- Data transfer rate up to 3 Mbps
- Data bits: 7 or 8
- Stop bits: 1 or 2
- Parity: None, Space, Even, Odd, Marker
- Flow control: None, hardware RTS/CTS, software XON/XOFF
- FIFO: 128 bytes - RX, 256 bytes - TX
- Cable length incl. connections: approx. 1.8 m
- Operating temperature: -20°C ~ 80°C

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

