

Item no.: 361311

Adapter cable USB 2.0 type-A to serial RS-232 with 9 open cable ends + shielding 2 m

from **18,49 EUR**

Item no.: 361311
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

This USB 2.0 Type-A to serial RS-232 adapter cable from Delock is suitable as a connection cable between a device with USB 2.0 and a device with RS-232 connection. Due to the tin-plated open cable ends, the connection can be made directly to an RS-232 device port or flexibly with various terminal blocks. In addition, it can be used to create customised adapters and cable assemblies.

Specification

- Connectors: 1 x USB type-A plug, 1 x serial RS-232 9 x open cable ends + shielding (tinned)
- Chipset: FTDI FT232R
- Compatible with UHCI / OHCI / EHCI controller
- Data bits: 7 or 8
- Stop bits: 1 or 2
- Parity: None, Space, Even, Odd, Marker
- Data transfer rate up to 230.4 Kbps
- Pin assignment: TxD (red), RxD (brown), RTS (blue), CTS (violet), DTR (orange), DSR (green), DCD (black), RI (white), GND (yellow), shielding (matt black)
- ESD overvoltage protection IEC 61000-4-2: HCP & VCP: ± 4 kV, air discharge: ± 8 kV, contact discharge: ± 4 kV
- Cable diameter: approx. 5 mm
- Wire cross-section: 26 AWG
- Conductor: stranded copper wire
- Insulation: PVC
- Cable length incl. connectors: approx. 2 m
- Colour: black
- Operating temperature: -10 °C ~ 80 °C

System requirements

- Mac OS 10.13 or higher
- Linux Kernel 2.6 or higher
- Windows 8.1/8.1-64/10/10-64/11
- Windows Server 2012 / Server 2012R2 / Server 2016
- PC or notebook with a free USB Type-A port

Package contents

- USB Type-A to 1 x serial adapter

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



