

Item no.: 361370

# Thunderbolt™ 3 (20 Gb/s) USB-C™ cable male >male passive 1.0 m 5 A

# from **48,22 EUR**

Item no.: 361370 shipping weight: 0.10 kg Manufacturer: Delock



## Product Description

This Thunderbolt™ 3 cable from Delock can be used universally and combines all the advantages of the Thunderbolt™ 3 interface. It enables the connection of various devices, such as external enclosures, monitors, card readers and docking stations, via a Thunderbolt™ 3 port of a PC or notebook. The cable enables data transfer rates of up to 20 Gb/s and supports the transfer of USB as well as DisplayPort, PCI Express and Ethernet data. For example, the connection of a 5K or a 4K DisplayPort monitor is possible, as is the connection of USB 3.1 Gen 2 devices. It is also possible to supply power to connected devices with an output of up to 100 W.Delock Thunderbolt™ 3 cable (Video)NoteThe maximum achievable data transfer rate of 40 Gb/s with Thunderbolt™ 3 can only be realised with a 0.5 m long cable (Delock 84844).

- Connectors:
   1 x Thunderbolt™ 3 USB Type-C™ 24 pin male >
   1 x Thunderbolt™ 3 USB Type-C™ 24 pin connector
   Chipset: Cypress E-Marker
   Conductor cross-section:

- Conductor cross-section:
  32 + 34 AWG data wire
  24 + 34 AWG power line
  Cable diameter: approx. 4.4 mm
  Conductor: 8 x coaxial for SuperSpeed USB, 1 x twisted pair for USB 2.0
  Contacts with gold plating
  Triple shielded cable
  Data transfer rates:
  Thunderbolt™ 3 up to 20 Gb/s
  DisplayPort 1.2a up to 21.6 Gb/s
  SuperSpeed USB up to 10 Gb/s
  Thunderbolt™ Networking up to 10 Gb/s (Peer-To-Peer)

- Thunderbolt™ Networking up to 10 Gb/s (Peer-To-Peer)
  Monitor resolution up to:

  1 x 5120 x 2880 30 bit @ 60 Hz or

  1 x 4096 x 2160 30 bit @ 60 Hz
  (depending on system and connected hardware)

- Supports data and video over a single cable
  Supports PCI Express 3.0 protocol (4 lanes)
  Supports DisplayPort 1.2a protocol (8 lanes, HBR2 and MST)
  Cascadable up to 6 Thunderbolt<sup>TM</sup> devices (daisy chain)
  Dual channel, bi-directional data transmission

- Power supply via USB Power Delivery up to 100 W (20 V / 5 A)
  Power supply for Thunderbolt™ 3 devices with bus power (max. 15 W)
  Colour: black
- Length without connectors: approx. 1.0 m

### System requirements

PC or notebook with a free Thunderbolt™ 3 port

#### Package contents

Thunderbolt™ cable

Scan this QR code to view the product All details, up-to-date prices and availability

