

Item no.: 361233

USB4[™] 20 Gbps cable 2 m

from **25,30 EUR**

shipping weight: 0.10 kg Manufacturer: Delock

Product Description

This USB4™ cable from Delock allows you to connect various devices, such as smartphones, monitors, external cases and docking stations, via a USB Type-C™ or Thunderbolt™ 3 port of a PC or notebook. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.

The cable enables data transfer rates of up to 20 Gbps when connecting USB4TM-compatible devices. Of course, USB 3.2 or USB 2.0 devices can also be connected.

The Delock cable supports DisplayPort 1.4a as well as DisplayPort 2.0 Alternate Mode and thus enables the connection of DisplayPort monitors with a screen resolution of up to 4K

Supporting the USB Power Delivery 3.0 standard, connected devices can be supplied with power, up to 100 W (20 V / 5 A) are possible. Specification

- Connectors:
 1 x USB4™ 20 Gbps (Gen 2x2) USB Type-C™ male >
 1 x USB4™ 20 Gbps (Gen 2x2) USB Type-C™ connector
 USB-IF certified cable
 Section of a compatible with USB 3.2. USB 2.0 and Thunde
- Backwards compatible with USB 3.2, USB 2.0 and Thunderbolt™ 3
- Chipset: Cypress E-Marker
- Wire gauge:30 + 31 AWG data wire
- 21 + 32 AWG power wire
- Contacts gold-platedCable diameter: approx. 5 mm
- Data transfer rate up to 20 Gbps
 Monitor resolution up to 3840 x 2160 @ 60 Hz
 (depending on system and connected hardware)
 Supports HDR10
 Supports HDR10

- Supports HDCP 1.4 and 2.3
- Supports PCI Express 3.0 protocol (4 lanes) Supports DisplayPort 1.4a protocol Supports DisplayPort Alt Mode 2.0

- Dual channel, bi-directional data transmission
 USB Power Delivery (USB PD 3.0) support up to 100 Watt (20 V / 5 A)

- Colour: blackLength incl. connectors: approx. 2 m

System requirements

- Device with a free USB Type-C[™] port and DisplayPort Alternate Mode or with a free

Package contents

USB4™ 20 Gbps cable

Packaging

Retail Box

Specifications

Scan this QR code to view the product All details, up-to-date

prices and availability

