

Item no.: 362136

S/PDIF TOSLINK Splitter 1 In 3 Out with USB power supply

from **14,79 EUR**

Item no.: 362136
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

With this TOSLINK splitter from Delock, up to three TOSLINK devices can be operated simultaneously on one TOSLINK output.

The splitter supports all common 2.0 and 5.1 audio formats such as LPCM, Dolby Digital, DTS Audio and thus offers a sound experience like in the cinema.

The splitter offers a sampling rate of up to 24 bit and 96 kHz. This means that the sound can be reproduced loss-free in the High-Res Audio range.

The splitter supports an output transmission distance of up to 40 m via an optical TOSLINK cable with a signal loss of less than 0.2 dB/m.

The splitter does not require an additional external power supply unit; power is supplied via the USB cable included in the scope of delivery.

Specification

- Connections:
- Input:
- 1 x TOSLINK socket S/PDIF
- 1 x USB type mini-B socket (5 V power supply)
- Output: 3 x TOSLINK socket S/PDIF
- Supported sampling rates: 32 / 44.1 / 48 / 96 kHz
- Bit rate 16 - 24 bit
- Baud rate: max. 16 Mbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supports signal retiming
- On/off switch
- Power LED (blue)
- Plastic housing
- Colour: black
- Dimensions (LxWxH): approx. 61 x 54 x 20 mm
- Voltage: 5 V
- Overvoltage protection
- USB bus power

System requirements

- Digital optical audio signal
- One free USB type-A socket

Package contents

- TOSLINK splitter
- USB Type-A to Type Mini-B cable, length approx. 75 cm
- Operating instructions

Packaging

- Retail Box

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

