

Item no.: BPE36V60ART2U

BPE36V60ART2U - Battery Pack Expansion incl. Rail Kit

690,25 EUR

Item no.: BPE36V60ART2U
shipping weight: 30.60 kg
Manufacturer: CyberPower



Product Description

BPE36V60ART2U - Battery Pack Expansion incl. Rail Kit

CyberPower BPE36V60ART2US is an Extended Battery Module (EBM) which can be used in conjunction with compatible UPS systems to provide prolonged system runtime during power interruption. The battery module comes with DC plug-and-play power connectors to allow for adding multiple EBMs.

The product features hot-swappable battery packs, allowing users to safely replace battery module without interrupting connected loads. The sealed lead-acid battery used within the EBM is stable and safe, which ensures the power system's reliable performance. Designed with industrial-grade metal enclosure, the product is suitable for data center and critical applications.

General

- Nominal output voltage (Vdc): 36
- Rated output current (A): 60

Battery

- Battery type: Sealed lead-acid
- Battery quantity (pcs.): 6
- Single battery voltage (V): 12
- Single battery capacity (AH): 9
- Built-in charger: No
- User-replaceable: Yes
- Hot-swappable: Yes
- Expansion ready: Yes
- Replacement battery pack: RBP0074
- Replacement battery pack quantity (pcs.): 2

Physical

- Form factor: Rackmount, tower
- Enclosure construction: Metal
- Color: Black
- Rackmount rail: Yes
- Rackmount ears: Yes

Physical Size

- Dimensions (WxHxD, in.): 17 x 3.5 x 16.9
- Dimensions (WxHxD, mm.): 433 x 88 x 430
- Weight (lbs.): 50.6
- Weight (kg.): 23
- Installed rack height (U): 2

Environment

- Operating temperature (°F): 32 ~ 104
- Operating temperature (°C): 0 ~ 40
- Operating relative humidity (non-condensing, %): 0 ~ 90
- Operating elevation (feet/meters): 0-9,843 feet (0-3,000 meters)
- Storage temperature (°F): 5 ~ 113
- Storage temperature (°C): -15 ~ 45
- Storage relative humidity (non-condensing, %): 0 ~ 95
- Storage elevation (feet/meters): 0-49,213 feet (0-15,000 meters)

Certifications

- Certifications: CE, C-Tick
- RoHS: Yes

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

