

Item no.: 317750

UBDO-N - UWAO RT3070 outdoor CPE, Outdoor USB WLAN Router

21,83 EUR

Item no.: 317750
shipping weight: 0.80 kg
Manufacturer: ALFA Network



Product Description

ALFA Network UWAO RT3070 outdoor CPE, Outdoor USB WLAN Router 802.11n/b/g long-range outdoor USB AP/CPE with N type antenna port for various antenna use

UWAO RT3070 is the long-range wireless 802.11b/g outdoor USB CPE with 5M usb cable. UWAO RT3070 provides users to launch IEEE 802.11n wireless network at 150 Mbps in the 2.4GHz frequency, which is also compatible with IEEE 802.11b/g wireless devices at 11/54Mbps.

You can easy to install and enjoy the internet connection by just simply plug USB into the Notebook and Desktop. UWAO RT3070 also includes a convenient Utility for scanning available networks and saving preferred networks that users usually connected with. Security encryption can also be configured by this utility.

The UWAO RT3070 uses the same Ralink RT3070 chipset and the same 2000mW wireless receiver as the popular AWUS036NH wifi USB adapter except it is built into an outdoor weather resistant casing.

The UWAO RT3070 does not need an external power supply. The device gets its power from the supplied 5m Dual "Y" USB to mini USB cable.

Features

- Complies with Universal Serial Bus Rev. 1.0, 1.1 and 2.0 specifications.
 - High-Power 2W with N-type female antenna connector for long-Range distance
 - High Speed transfer data rate up to 150 Mbps
 - Support wireless data encryption with 64/128-bit WEP, WPA (TKIP with IEEE 802.1x) and AES functions.
 - Support driver for Windows 98se, Me, 2000, XP and Vista, Windows 7, Windows 8, Apple Mac and Linux.
 - Supports auto-installation and diagnostic utilities.
- Model: UWAO RT3070
 - Standard: IEEE 802.11n/b/g, USB v1.0/1.1/2.0
 - USB cable Length: 5M
 - Data Rate:
 - IEEE 802.11n 150Mbps
 - IEEE 802.11g 54Mbps
 - IEEE 802.11b 11Mbps
 - Output Power: 34dBm
 - Receiver Sensitivity:
 - IEEE802.11n-73dBm (at)HT20, -66dBm (at)HT40 IEEE 802.11g -76dBm (at) 54Mbps
 - IEEE 802.11b -92dBm (at) 11Mbps
 - Antenna: External N type Female Antenna Port
 - Wireless Security
 - WEP 64/128 bit
 - WPA/WPA2-PSK
 - WPS
 - Frequency Range
 - US, Canada 2.412GHz~2.462GHz (CH1~CH11)
 - EU 2.412GHz~2.472GHz(CH1~CH13)
 - Japan 2.412GHz~2.484GHz(CH1~CH14)
 - Physical Port
 - N-Buchse 1x
 - Mini USB x 1
 - Security: 64/128-bit WEP Encryption, WPA, WPA2, TKIP, AES
 - Support OS: Windows XP/2000/Vista, Windows 7, Windows 8, Linux, Mac
 - Operating Voltage: DC 5V +/- 5%
 - Temperature: Operating: 0°C ~ +50°C
 - Storage : -10°C ~ +65°C

This product underlies the GPL v2.

Note: Please use the unit in Germany with the zone "ETSI" only! In accordance with the applicable requirements in Germany, the radiated power (EIRP of a wireless device should not exceed 20 dbm (100mW). Please note the telecommunications law in your respective country.

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

