

Item no.: CPE210

CPE210 - 2.4 GHz 300 Mbps 9 dBi Outdoor CPE

from **43,39 EUR**

Item no.: CPE210
shipping weight: 0.80 kg
Manufacturer: TP-LINK



Product Description

TP-Link CPE210 - 2.4 GHz 300 Mbps 9 dBi Outdoor CPE

TP-LINK's 2.4 GHz 300 Mbps 9 dBi Outdoor CPE, the CPE210, is dedicated to cost-effective solutions for outdoor wireless networking applications. With its centralized management application, it is flexible and ideal for point-to-point, point-to-multipoint and outdoor Wi-Fi coverage applications. Professional performance, coupled with user-friendly design, makes CPE210 an ideal choice for both business and home users.

HARDWARE FEATURES

- Processor: Qualcomm Atheros 560 MHz CPU, MIPS 74Kc
- Memory: 64 MB DDR2 RAM, 8 MB Flash
- Interface:
 - 1x 10/100 Mbps shielded Ethernet port (LAN0, passive PoE in)
 - 1x 10/100 Mbps shielded Ethernet port (LAN1, passive PoE passthrough)
 - 1x Grounding terminal
 - 1x Reset button
- Power supply: Passive Power over Ethernet via LAN0 (+4, 5 pins; -7, 8 pins)
- Voltage range: 16 - 27 V DC
- Dimensions (W x D x H): 224 x 79 x 60 mm
- Power consumption: 10.5 Watts max.
- Antenna type: Built-in 9 dBi 2x2 dual-polarized directional antenna
- Beam width: 65° (H-plane)/35° (E-plane)
- Protection:
 - 15 KV ESD protection
 - 6 KV lightning protection
- Enclosure:
 - Outdoor ASA stabilized plastic material
 - IPX5 waterproof certification

WIRELESS FEATURES

- Wireless standards: IEEE 802.11b/g/n (with Pharos MAXstream disabled)
- Proprietary protocol: TDMA Mode (with Pharos MAXstream enabled)
- Wireless speeds:
 - Up to 300 Mbps (40 MHz, dynamic)
 - Up to 144.4 Mbps (20 MHz, dynamic)
 - Up to 72.2 Mbps (10 MHz, dynamic)
 - Up to 36.1 Mbps (5 MHz, dynamic)
- Frequency: 2.4 ~ 2.483 GHz
- Transmission power: 27 dBm/500 mw (adjustable power by 1 dBm)

OTHERS

- Certification: CE, FCC, RoHS, IPX5
- Package contents:
 - Outdoor wireless CPE
 - 24 V/1 A passive PoE adapter
 - Pole mounting straps
 - AC power cord
 - Installation guide
- System requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista(TM) or Windows10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux.
- Environment:
 - Operating temperature: -30°C ~ 70°C (-22°F ~ 158°F)
 - Storage temperature: -40°C ~70°C (-40°F ~ 158°F)
 - Operating humidity: 10% ~ 90% non-condensing
 - Storage humidity: 5% ~ 95% non-condensing

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

