

Item no.: PAT23014 PAT2314 - 2.3 GHz, 14 dBi Outdoor Panel Antenna





Product Description

IT ELITE PAT23014 - 2.3 GHz, 14 dBi Outdoor Panel Antenna

Panel antenna working in 2.3 GHz frequency with full 14 dBi gain. It can be mounted for horizontal or vertical polarization. Made with very high quality materials, such as industrial-grade aluminum alloy, UV-resistant plastic cover and zinc galvanized U-bolt.

Designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosioneven in saltwater environments. Heavy-duty mounting elements guarantee an easy elevation adjustment, as well as rock-stable operation.

It can be used in client stations and as a small base station. Key Features:

- 14 dBi directional gain
- Highest Ingress Protection Rating IP 66
 High-quality construction
 Horizontal or vertical polarization
 Heavy-duty mounting elements
 Easy elevation and tilt adjustment
 Designed for all weather construction

- Designed for all-weather operation
- Applications:
 - WCS band 2.3 2.36 GHz
 - Point to point applications

Electrical Properties

- Frequency: 2.3 2.36 GHz
 Gain: 14 dBi
- Polarization: Horizontal or vertical
- Beamwidth deg horizontal: 38°
 Beamwidth deg vertical: 38°
- VSWR:
- Impedance: 50 Ohm
 Front-to-back ratio: >35 dB

Enclosure Properties

- Technology: Microstrip
 Material: UV-resistant
 Color: Grey
- Min. temperature: -40°C / -40°F
- Max. temperature: 80°C / 176°F

Mechanical Properties

- Input connector: N-type / female
 Outside dimensions: 169 x 169 x 20 mm / 6.65 x 6.65 x 0.78"
 Weight: 0.6 kg / 1.3 lbs

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

