

Item no.: SECTOR24015H SEC2415H - 2.4 GHz, 15 dBi Outdoor Sector Antenna





Product Description

T ELITE SEC24015H - 2.4 GHz, 15 dBi Outdoor Sector AntennaSector antenna working in the 2.4 GHz band with 15 dBi gain andhorizontal polarization.

Because of reduced sidelobes, the antenna keeps a clear, strong signal even in crowded radio enviroments. It's resistant to interference from other networks and does not disrupt others. Antenna features no beam squint due to frequency change, it means that decreasing of data throughput or even loss of a link after frequency channel change does not occur.

Specifically designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosioneven in saltwater environments. Professional mounting system with 0-15 degrees scale guarantees easy and smooth tilt adjustment, as wellas rock-stable operation. Key Features:

- 15 dBi sectorial gain
 Special outdoor weatherproof enclosure
 Highest International Protection Rating IP 66
 High-quality construction

- Minimized sidelobe levels
 Horizontal polarization

- Heavy-duty mounting elements
 Easy elevation and tilt adjustment
 Designed for all-weather operation

Applications:

- 2.4 GHz Band Wireless LAN
- IEEE 802.11b/g WLAN systems
- Point to point application

Electrical Properties

- Frequency: 2.4 2.5 GHz
- Gain: 15 dBi
 Polarization: horizontal
- Beamwidth deg horizontal: 90° (-3 dB), 120° (-6 dB) Beamwidth deg vertical: 12°
- VSWR:
- Impedance: 50 ohms
- Front to back ratio: > 35 dB
- **Mechanical Properties**

 - Technology: Microstrip
 Input connector: N-type / female
 Dimensions: 580 x 125 x 50 mm

 - Weight: 1.5 kg
 - Radome material: UV-resistant Color: white •
 - Construction: all-weather operation



Scan this QR code to view the product All details, up-to-date prices and availability