

Item no.: 315257

RBA-04-AS3-CAX-C1 - 10" Wall Mounted Cabinet, 4 U, Glass Door

150,26 EUR

Item no.: 315257
shipping weight: 5.50 kg
Manufacturer: Triton



Product Description

Triton RBA-04-AS3-CAX-C1 - 10" Wall Mounted Cabinet, 4 U, Glass Door Cabinet for small office/home office network (SOHO), IP30, Capacity 20 kg

Ideal solution for installation of 10 components. The cabinet is often used for small projects such as home networks or small company networks (SOHO). It is a popular accessory to standard 19" cabinets. Rigid construction

High-quality workmanship and up-to-date technology ensure a perfect look of the cabinet. Door

The cabinet comes with glass doors by default. However, it can be delivered with steel or perforated doors if required. Flexible door opening

The hinge system allows convenient access. Door lock

Locks the cabinet safely and protects the installed devices. Adjustable vertical rails

10" rails are adjustably attached to the cabinet construction in predefined positions. Breakout-type blanking panels

Cable openings covered with breakout-type blanking panels are located in the top, bottom and rear part of the cabinet. Size in mm: A 248 x B 169 x C 255 x D 310 x E 260 x R1 212 x R2 212

Description, Usage

- 10" wall-mounted cabinet with IP30 protection
- Cabinet is to be hanged right on the wall.
- Cabinet includes two adjustable vertical rails.
- Cabinet construction: compact welded cabinet, safety hardened glass door, thickness 4 mm. On demand may be metal or perforated.
- Max. permissible load of the door is 10 kg.
- Cabinets are intended for installation of data and telecommunication devices and their distribution systems.
- The frame of the cabinet and all the removable parts (side and rear covers, doors) are connected with grounding cables that have to be properly attached and inserted into the connectors during use of the cabinet at all times.
- There is an M5 screw placed on the bottom part of the cabinet as the main grounding point.
- Cable openings covered with breakout-type blanking panels are placed in the top and the bottom part of the cabinet's back panel as well as in the top and bottom of cabinet.

Supply includes:

- 2x key - front door
- 4x screw 6x50
- 4x washer 6,6
- 4x dowel 10
- 8x captive nut M6

Material:

- Safety hardened glass 4 mm thick
- Steel sheet

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



