

Item no.: 323581

UBDO-N8 - 802.11n Long-Range Outdoor USB AP/CPE

23,62 EUR

Item no.: 323581
shipping weight: 0.90 kg
Manufacturer: ALFA Network



Product Description

ALFA UBDo-n8 - 802.11n Long-Range Outdoor USB AP/CPE

UBDo-n8 is a long-range wireless 802.11n outdoor USB AP/CPE with an 8 m USB cable. UBDo-n provides users to launch IEEE 802.11n wireless networks at 150 Mbps in the 2.4 GHz frequency. You can easily install and enjoy the internet connection by simply plugging the USB into the Notebook and Desktop. UBDo-n8 also includes a convenient utility for scanning available networks and saving preferred networks that users usually connect with. Security encryption can also be configured by this utility.

- Complies with Universal Serial Bus Rev. 1.0, 1.1 and 2.0 specifications
- High-power 2000 mW with integrated 12 dBi antenna for long-range distance
- High-speed transfer data rate up to 150 Mbps at 802.11n
- Dynamic data rate scaling at 1, 2, 5.5 and 11 Mbps for 802.11b and 6, 9, 12, 18, 24, 36, 48 and 54 Mbps for 802.11g
- Supports wireless data encryption with 64/128-bit WEP, WPA (TKIP with IEEE 802.1x) and AES functions
- Supports driver for Windows XP, Vista, Windows 7, Mac OS X, and Linux
- Supports auto-installation and diagnostic utilities

- Standards: IEEE 802.11b/g/n; USB v1.0/1.1/2.0
- USB cable length: 8 m
- Data rate: IEEE 802.11n 150 Mbps; IEEE 802.11g 54 Mbps; IEEE 802.11b 11 Mbps
- Output power: 32 dBm +/- 2 dBm
- Receiver sensitivity: IEEE 802.11n -73 dBm (at) HT20, -66 dBm (at) HT40; IEEE 802.11g -76 dBm (at) 54 Mbps; IEEE 802.11b -92 dBm (at) 11 Mbps
- Antenna connector: N type female connector
- Frequency range: US, Canada 2.412 ~ 2.462 GHz (CH1 ~ CH11); EU 2.412 ~ 2.472 GHz (CH1 ~ CH13); Japan 2.412 ~ 2.484 GHz (CH1 ~ CH14)
- Security: 64/128-bit WEP encryption, WPA, WPA2, TKIP, AES
- Supportes OS: Windows XP/2000/Vista, Windows 7, Linux, Mac
- Operating voltage: DC 5 V +/- 5%

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

