

Item no.: 351771

11489 - Wall Socket with 2x USB Charging Ports 3.4 A, 1x USB Type-A and 1x USB Type-C™

from **25,69 EUR**

shipping weight: 0.10 kg Manufacturer: Delock



Product Description

Wall Socket with 2x USB Charging Ports 3.4 A, 1x USB Type-A and 1x USB Type-C™

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB charging ports. With the two charging ports USB Type-A and USB Type-C[™], this socket is also prepared for the future. Thus, smartphones, tablets and similar devices can be charged while the socket is still available. Suitable for many switch series

The socket is compatible to switch series with 55 x 55 mm frame window sizes. This includes the switch series of well-known manufacturers such as Gira, JUNG, Busch-Jaeger or

- Connectors: 1x power socket CEE 7/3 with childproof lock, 1x USB Type-A charging port, 1x USB Type-C[™] charging port, 3x screw terminal for PE, N, L
 Rated current: 16.0 A/250 V~
- Rated power: 4000.0 W
 USB charger: Input: AC 250 V/50 Hz/0.2 A; USB output: max. 5.0 V/3.4 A total; Output power: max. 17.0 W total; Average active efficiency 82.91 %, Efficiency at low load (10 %) 78.09 %; No-load power consumption 0.095 W; Short circuit protection
- Suitable for switch series with 55 x 55 mm frame window size Mounting depth: 40 mm Suitable for standard installation box
- Claw and screw fixing
 Fire retardant plastic housing (UL 94 V-0)
- Dimensions (L x W x H): ca. 80 x 80 x 44 mm
 Colour: White

System Requirements

- Mains supply with groundingA free standard installation box

Specifications

prices and availability