

Item no.: 332957

## TL-SG1210P - 10-Port Gigabit Desktop Switch with 8-Port PoE+

**86,31 EUR**

Item no.: 332957  
shipping weight: 1,30 kg  
Manufacturer: TP-LINK



### Product Description

#### TL-SG1210P - 10-Port Gigabit Desktop Switch with 8-Port PoE+

The TL-SG1210P provides 9x 10/100/1000 Mbps RJ45 ports and 1x Gigabit SFP port. Port 1 to port 8 of the switch support IEEE 802.3af/at compliant PDs with up to 30 W for each PoE port and total PoE power budget of 63 W. The TL-SG1210P is an unmanaged switch with desktop design, outstanding performance and quality, which is a great selection for expanding your home or office network. Power over Ethernet

- 8x IEEE 802.3af/at compliant PoE+ ports, with a total PoE power budget of 63 W
- Flexible deployment for PoE supported devices such as wireless access points (APs), IP cameras and IP phones
- Designed to use a single Ethernet cable for both data and power transmission, lowering infrastructure costs

#### Gigabit Expansion Solution

- 9x 10/100/1000 Mbps RJ45 ports and 1x Gigabit SFP port provide up to 20 Gbps switching capacity
- IEEE 802.3x flow control provides reliable data transfer

#### Highlight Performance

- 802.1p and DSCP QoS ensures smooth traffic
- IGMP snooping optimizes multicast applications
- Fanless design ensures quiet operation

#### Easy to Use

- Just plug & play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables
- Auto-negotiation intelligently adjusts for compatibility and optimal performance
  
- Model: TL-SG1210P
- Standards: IEEE 802.3i, 802.3u, 802.3ab, 802.3x, 802.3af, 802.3at, 802.3z, 802.1p
- Network ports: 8x PoE+ 10/100/1000 Mbps RJ45 ports; 1x 10/100/1000 Mbps RJ45 port; 1 Gigabit SFP slot
- Network media (cable): 10Base-T: UTP category 3, 4, 5 cable (maximum 100 m); EIA/TIA-568 100 ohms STP (maximum 100 m); 100Base-TX: UTP category 5, 5e or above cable (maximum 100 m); EIA/TIA-568 100 ohms STP (maximum 100 m); 1000Base-T: UTP category 5, 5e, 6 or above cable (maximum 100 m); EIA/TIA-568 100 ohms STP (maximum 100 m); 1000BASE-X: MMF, SMF
- PoE: PoE standard: 802.3af/at; PoE ports 1-8, up to 30 W per port; PoE power budget: 63 W
- Auto negotiation: Yes
- Auto MDI/MDIX: Yes
- Max. power consumption: 7.11 W (220/50 Hz no PD connected); 78.13 W (220/50 Hz with 63 W PD connected)
- Max. heat dissipation: 24.25 BTU/h (no PD connected); 266.42 BTU/h (with 63 W PD connected)
- Forwarding mode: Store and forward
- Switch capacity: 20 Gbps
- MAC address table: 4K, auto-learning, auto-aging
- Flow control: Yes
- Fanless: Yes
- LED: Power, link/act, PoE status, PoE max
- Dimensions: 8.2 x 5.0 x 1.0 in. (209 x 126 x 26 mm)
- Certification: CE, FCC
- Operating temperature: 0°C to 40°C (32°F to 104°F)
- Storage temperature: -40°C to 70°C (-40°F to 158°F)
- Operating humidity: 10% to 90% non-condensing
- Storage humidity: 5% to 90% non-condensing

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

