

Item no.: 345077

PR3PUPS3 - Universal Power Supply, 9 W

from **9,00 EUR**

Item no.: 345077
shipping weight: 0.20 kg
Manufacturer: Teltonika



Product Description

Universal Power Supply, 9 W

Universal power supply with exchangeable connectors for EU, US, UK and Australia.

- Input voltage: 100-240 V AC (max. 90-264 V AC)
- Input frequency: 50/60 Hz (max. 47-63 Hz)
- Input current (@100-240 V AC): 0.45 A
- Inrush current (@100-240 V AC): 30 A (max. 60 A)
- Leakage current: 0.25 mA
- Output voltage: 9 V DC (max. 8.55-9.45 V DC)
- Load current: 1 A
- Ripple and noise: 200 mV
- Output over current protection: 2 A
- Standby power: 0.1 W
- Average efficiency: 81.34 % (DoE level VI)
- Certification: EMC: EN 55032:2015, FCC Part 15B; EMI: EN 55035:2017, IEC 61000-4-2:2008, IEC 61000-4-3:2006+A1:2007+A2:2010, IEC 61000-4-4:2012, IEC 61000-4-5:2014, IEC 61000-4-6:2013, IEC 61000-4-11:2004; Safety: EN 62368-1:2014+A11:2017, UL 62368-1:2014 Ed.2, CSA C22.2 No. 62368-1:2014 Ed.2, AS/NZS 62368.1:2018
- Hi-pot test: Primary to secondary: 4000 V DC
- Lifetime: 30.000 hours minimum
- Input connector: Exchangeable, EU (Type C), US (Type A), UK (Type G) and AU (Type I) included
- Output connector: 4-pin, 3 mm pitch

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

