

Item no.: RUT951

RUT951 000000 - 4G LTE Wi-Fi Dual-SIM Router

from **213,38 EUR**

Item no.: RUT951
shipping weight: 0.60 kg
Manufacturer: Teltonika



Product Description

RUT951 - 4G LTE Wi-Fi Dual-SIM Router

RUT951 took the best features from one of the most popular Teltonika Networks cellular routers - RUT950. This device features dual SIM 4G cellular connectivity combined with Wi-Fi and 4 Ethernet interfaces to meet the needs of the most varied IoT solutions. Automatic WAN failover to an available backup connection ensures network continuity and eliminates downtime. Powered by RutOS that offers customization options for professional use, automation features, and top-level security for your solution. Compatible with the Teltonika Networks Remote Management System (RMS) enables secure remote management to save time and expenses.

Hardware

- Mobile: 4G/LTE (Cat 4), 3G, 2G
- CPU: Mediatek MIPS 24Kc 580 MHz
- Storage: 16 MB Flash
- Memory: 128 MB RAM
- Powering option: 4-pin power socket, 9-30 V DC
- SIM: 2x external SIM holders (2FF)
- Antenna connectors: 2x SMA for mobile, 2x RP-SMA for WiFi
- Ethernet: 4x 10/100 Ethernet ports: 1x WAN (configurable as LAN); 3x LAN
- WiFi: IEEE 802.11b/g/n, Access Point (AP), Station (STA)
- Inputs/outputs: On 4-pin socket: 1x digital input, 1x digital open collector output
- Status LEDs: 1x bi-color connection type, 5x signal strength, 4x Ethernet, 1x power
- Operating temperature: -40°C to 75°C
- Housing: Aluminium housing with DIN rail mounting option, plastic panels with flat mounting option
- Dimensions (W x H x D): 110 x 50 x 100 mm
- Weight: 268 g

Software

- Operating system: RutOS (OpenWrt based Linux OS)
- Mobile features: Auto APN, band lock, SIM switch, operator black/white list, data/SMS limits
- Network: Failover (network backup), VLAN, QoS, load balancing
- Routing: Static routes, dynamic routes (BGP, OSPFv2, RIPv1/v2, EIGRP, NHRP), routing rules
- VPN and tunneling: OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard
- Monitoring and management: WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS
- Connection monitoring: Ping reboot, Wget reboot, periodic reboot, LCP and ICMP for link inspection
- Cloud solutions: RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
- Hotspot: External/internal radius, SMS OTP, MAC authentication, Walled Garden
- Supported Hotspot platforms: IronWiFi, HotspotSystem, Cloud4Wi, SAI + WiFi, MugiCloud, Purple.ai
- SMS features: SMS status, SMS configuration, send/read SMS via HTTP POST/GET, Email to SMS, SMS to Email, SMS to HTTP, SMS to SMS, scheduled SMS, SMS autoreply, SMPP
- Services: DDNS, VRRP, Wake On Lan (WOL), WEB filter, UPNP, traffic logging

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



