

Item no.: FMC003

FMC003 - Plug and Play Tracker, LTE Cat. 1

from **73,78 EUR**

Item no.: FMC003
shipping weight: 0.20 kg
Manufacturer: Teltonika



Product Description

FMC003 - Plug and Play Tracker, LTE Cat. 1

FMC003 is an advanced plug and play LTE Cat. 1 device dedicated for next generation OBD applications. The main feature of FMC003 is its possibility to read OEM parameters (PIDs) via OBD port. With this device, you will be able to read Real Odometer and Real Fuel Level data. What's more, the device comes with the supported vehicles and data list, so no need to guess anymore – now you know what data you can read from a specific vehicle. It is a perfect tracker for a wide range of use cases – including fleet management of light commercial vehicles, driver log-book, insurance telematics (UBI), car rental & leasing and more.

Module

- Name: Teltonika TM2500, MeiG SLM320-E, MeiG SLM320-LA
- Technology: LTE (Cat. 1)/2G (GSM/GPRS)/GNSS/Bluetooth

GNSS

- GNSS: GPS, GLONASS, GALILEO, BEIDOU, SBAS, QZSS, DGPS, AGPS
- Receiver: 33 channels
- Tracking sensitivity: -165 dBm
- Accuracy: < 2.5m CEP
- Hot start: < 1 s
- Warm start: < 25 s
- Cold start: < 35 s

Cellular

- Technology: GSM
- 2G bands: GSM: B2/B3/B5/B8
- 4G bands: SLM320-E: LTE FDD: B1/B3/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 SLM320-LA: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B20/B28 LTE-TDD: B40
- Data transfer: LTE: LTE FDD: Max. 10 Mbps (DL)/max. 5 Mbps (UL), LTE TDD: Max. 8 Mbps (DL)/max. 2 Mbps (UL); GSM: GPRS: Max 85.6 Kbps (DL)/max. 85.6 Kbps (UL)
- Data support: SMS (text/data)

Power

- Supply voltage range: 10 - 30 V DC with overvoltage protection
- Back-up battery: 170 mAh Li-Ion battery 3.7 V (0.63 Wh)

Bluetooth

- Specification: 4.0 + LE
- Supported peripherals: Temperature and humidity sensor, Inateck barcode scanner, universal BLE sensors support

OBD Interface

- Data: K-Line, CAN bus data
- Data reading: Up to 32 vehicle onboard parameters, supported OBD protocols: ISO 9141-2 (5 baud init, 10.4 kbaud), ISO 14230-4 KWP (5 baud init, 10.4 kbaud), ISO 14230-4 KWP (fast init, 10.4 kbaud), ISO 15765-4 CAN (11 bit ID, 250 kbaud), ISO 15765-4 CAN (11 bit ID, 500 kbaud), ISO 15765-4 CAN (29 bit ID, 250 kbaud), ISO 15765-4 CAN (29 bit ID, 500 kbaud)

Interface

- Connection: OBDII socket
- GNSS antenna: Internal high gain
- Cellular antenna: Internal high gain
- USB: 2.0 Micro-USB
- LED indication: 2x status LED lights
- SIM: Micro-SIM
- Memory: 128 MB internal Flash memory

Physical Specification

- Dimensions: 67,2 x 49,6 x 25 mm (L x W x H)
- Weight: 63 g

Operating Environment

- Operating temperature (without battery): -40°C to +85°C
- Storage temperature (without battery): -40°C to +85°C
- Operating humidity: 5% to 95% non-condensing
- Ingress protection rating: IP41
- Battery charge temperature: +10°C to +45°C
- Battery discharge temperature: -20°C to +60°C
- Battery storage temperature: -20°C to +45°C for 1 month; -20°C to +35°C for 6 months

Features

- Sensors: Accelerometer
- Scenarios: Green driving, Over speeding detection, Jamming detection, GNSS fuel counter, Excessive idling detection, Unplug detection, Towing detection, Crash detection, Auto geofence, Manual geofence, Trip
- Sleep modes: GPS sleep, Online deep sleep, Deep sleep, Ultra deep sleep
- Configuration and firmware update: FOTA Web, FOTA, Teltonika configurator (USB, Bluetooth), FMBT mobile application (configuration)
- SMS: Configuration, events, debug
- GPRS commands: Configuration, debug
- Time synchronization: GPS, NITZ, NTP
- Fuel monitoring: OBD II
- Ignition detection: Accelerometer, external power voltage, engine RPM

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

