

## Item no.: 357309 Shrink tubing assortment case, coloured, 590 pieces



shipping weight: 1.20 kg Manufacturer: Delock



## Product Description

This high-quality heat shrink tubing set from Delock is used to protect and insulate cables, electrical lines or wires. When exposed to heat, the tubing completely encloses the cable and contracts. This protects the cable from the weather and mechanical damage.

This set includes hoses with ten different diameters, four different lengths and five different colours for versatile use.

The case is ideal for transport and protects the heat-shrink tubing from dirt, dust and damage.

By repositioning the dividers, the size of the individual compartments can be individually adjusted to add shrink tubing with different lengths.

The heat-shrink tubing can be used in a workshop, in the home or in industry, for example.

The heat shrink tubing can be heated with a heat gun, the tubing shrinks to half its original diameter when heated.

- Contents:20 x diameter 1.0 mm black, length: approx. 50 mm20 x diameter 1.0 mm blue, length: approx. 50 mm20 x diameter 1.0 mm red, length: approx. 50 mm20 x diameter 1.0 mm yellow, length: approx. 50 mm20 x diameter 1.5 mm black, length: approx. 50 mm20 x diameter 1.5 mm blue, length: approx. 50 mm20 x diameter 1.5 mm blue, length: approx. 50 mm20 x diameter 1.5 mm blue, length: approx. 50 mm20 x diameter 1.0 mm wellow, length: approx. 50 mm20 x diameter 1.5 mm black, length: approx. 50 mm20 x diameter 2.0 mm black, length: approx. 100 mm20 x diameter 2.0 mm blue, length: approx. 50 mm20 x diameter 2.0 mm black, length: approx. 100 mm20 x diameter 2.0 mm blue, length: approx. 100 mm20 x diameter 3.0 mm blue, length: approx. 100 mm20 x diameter 3.0 mm blue, length: approx. 100 mm20 x diameter 3.0 mm blue, length: approx. 100 mm20 x diameter 3.0 mm blue, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 6.0 mm black, length: approx. 100 mm10 x diameter 4.5 mm black, length: approx. 100 mm10 x diameter 10.0 mm 10 x diameter 6.0 mm black, length: approx. 100 mm10 x diameter 10.0 mm black, length: approx. 100 mm6 x diameter 10.0 mm black, length: approx. 100 mm6 x diameter 13.0 mm ed, length: approx. 100 mm6 x diameter 13.0 mm ed, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm ed, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length: approx. 100 mm6 x diameter 13.0 mm white, length:
- Shrinkage rate 2:1
- Shrink temperature: 70 °C ~ 125 °C Material: polyethylene
- Dimensions of assortment case (LxWxH): approx. 380 x 310 x 70 mm

## Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

