

Item no.: 357392

## 63276 - HDMI Audio Extractor 4K 60 Hz, compact

**32,13 EUR**

Item no.: 357392  
shipping weight: 0.10 kg  
Manufacturer: Delock



### Product Description

With this adapter by Delock, the audio signal can be decoupled from an HDMI transmission. While the image signal is displayed on a TV or monitor, the audio signal can be output digitally (S/PDIF) or analogue (stereo) to other devices, such as headphones or surround receivers. Connections: Input: 1 x HDMI-A 19 pin plug 1 x USB type Micro-B socket (5 V power supply) Output: 1 x HDMI-A 19 pin socket 1 x 3.5 mm 3 pin jack socket (audio) 1 x TOSLINK socket S/PDIF- High Speed HDMI, 3D and HDCP 1.4 / HDCP 2.2- Supports HDR (High Dynamic Range) Automatic switching to stereo (2.0) when using the jack socket and automatic muting of the digital output- Resolution up to 3840 x 2160 @ 60 Hz- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio- Supported sampling rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)- HDMI audio is passed through to the output (pass-through)- Power consumption: max. 2 W max. System requirements- One free HDMI-A socket- One free USB type A socket Package contents- HDMI Audio Extractor- USB type A to type Micro-B cable, length approx. 30 cm- Operating instructions

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

