

Item no.: 357816

LTE antenna SMA connector 0 - 4 dBi omnidirectional rotatable with tilt joint black

from **18,53 EUR**

Item no.: 357816
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

This LTE antenna from Delock enables the use of various LTE bands for indoor installation. It is fully compatible with GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT and Z-Wave.

- Connection: SMA plug
- LTE Band: 1-10; 12; 19; 25; 30; 33-41
- Frequency range: 698 - 791 MHz 824 - 960 MHz 1710 - 2170 MHz 2300 - 2400 MHz 2500 - 2700 MHz
- Compatible with GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave
- Antenna gain: 1.5 dBi @ 698 - 791 MHz 0 dBi @ 824 - 960 MHz 1.5 dBi @ 1710 - 2170 MHz 4 dBi @ 2300 - 2400 MHz 4 dBi @ 2500 - 2700 MHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 4.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length: approx. 231.50 mm (with tilt joint); approx. 199.20 mm (without tilt joint)
- Diameter: approx. 19.70 mm (tip); approx. 21.50 mm (max.); approx. 13.20 mm (SMA)

System requirements

- Device with a free SMA socket

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

