

Item no.: 357778

LTE antenna RP-SMA connector -0.9 - 2.3 dBi omni with tilt joint black

from **3,03 EUR**

Item no.: 357778
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

This GSM/UMTS/LTE antenna can be connected to a GSM/UMTS/LTE device with RP-SMA connector to receive and transmit signals.

- Connectors: RP-SMA connector
- Frequency range: 790 - 870 MHz, 1710 - 1880 MHz, 1920 - 2170 MHz, 2400 - 2700 MHz
- Antenna gain: -0.9 - 0.6 dBi @ 790 - 870 MHz, 0.7 - 1.8 dBi @ 1710 - 1880 MHz, 1.3 - 1.9 dBi @ 1920 - 2170 MHz, 0.9 - 2.3 dBi @ 2400 - 2700 MHz
- Impedance: 50 Ohm
- Polarisation: Linear, vertical
- VSWR: 4.0
- Operating temperature: -10°C ~ 55°C
- Housing material: ABS
- Colour: Black
- Length: approx. 197.10 mm (with tilt joint), approx. 167.00 mm (without tilt joint)
- Diameter: approx. 25.40 mm (tip), approx. 28.00 mm (max.), approx. 13.50 mm (RP-SMA)

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

